TECH LIGHTING

PRODUCT FEATURES

- Rounded, high gloss, metal panels create a symmetrical, contemporary shade with negative space
- · Available in a White finish
- · Aluminum construction for light, durable structure
- · High quality acrylic diffuser softens the light
- The LED Driver is housed within the junction box for this product
- Protected by a 5-year warranty



LAMPING

LED includes 22.4 watt 1174.6 delivered lumens 90 CRI 3000K LED module. Dimmable with a low-voltage electronic dimmer. 120v or 277v

White



White

ORDERING INFORMATION

700FMLFO FINISH	LAMP	
W WHITE	-LED930	INTEGRATED LED 90 CRI 3000K 120V
	-LED930-2	77 INTEGRATED LED 90 CRI 3000K 277V


700FMLFO JOB NAME NOTES



TECH LIGHTING

SPECIFICATIONS

HARDWARE MATERIAL	Metal
SHADE MATERIAL	Aluminum
NET WEIGHT	4.5 lbs
HEIGHT	2.5in
WIDTH	14in
LENGTH	14in
UP LIGHT / DOWN LIGHT / BOTH?	
WET LISTED	
DAMP LISTED	Yes
DRY LISTED	
WALL / CEILING MOUNT	
GENERAL LISTING	ETL Listed
INCLUDES	



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	222 24.111	1175.0	NON LEB	110 2 1111
WATTS		22.3		
MAX WATTAGE PER BULB		22.3W		
INDUTYOUTAGE		120V		
INPUT VOLTAGE		277V		
DIMANUS TYPE*		ELV, TRIAC		
DIMMING TYPE*		0-10V		
ССТ		3000K		
CRI		90 CRI		
LED LIFETIME				
L70		>50000		
AVERAGE BULB HOURS				
FIELD SERVICEABLE LED				
LAMP BASE		Integrated LED		
LAMP SHAPE		Integrated LED		
LAMP INCLUDED?		True		
WARRANTY**		5 Years		

^{*} Dimming information available at www.techlighting.com/Downloads#dimming ** Visit techlighting.com for specific warranty limitations and details.

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.	No		
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.	N/A		

^{*}If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

