

Kable Lite Surface Kit 300w

**DESCRIPTION**

Includes 45' of bare cable (enough for a twenty foot wall-to-wall run), two pairs of slimline turnbuckles and a 12 volt 300 watt surface magnetic transformer. Add up to six 50 watt elements or up to eight 35 or 37 watt elements.

INSTALLATION

Magnetic transformer mounts to a standard 4" junction box with round plaster ring (provided by electrician) and includes 24" softwire leads.

DIMMING

Dimmable with a 600 watt low-voltage magnetic dimmer. The dimmer is placed on the line side of the transformer. (Consult dimmer manufacturer for specifics). This surface transformer includes a preinstalled debuzzing dimming coil to reduce audible noise when using a low-voltage dimmer.

ORDERING INFORMATION**700KLKTS300** FINISH

C CHROME
S SATIN NICKEL

**TECH LIGHTING®**

7400 Linder Avenue
Skokie, Illinois 60077

T 847.410.4400
F 847.410.4500

www.techlighting.com

700KLKTS300 _____

FIXTURE TYPE: _____

JOB NAME: _____

NOTES: _____

_____

©2011 Tech Lighting, L.L.C. All Rights Reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C.
Tech Lighting reserves the right to change specifications for product improvements without notification.