

## PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- High-tech display head that combines simplicity with practical technology
- Telephoto camera lens inspired design
- Highly customizable featuring a plethora of finishes, beam spreads, lamping and stem lengths
- Monopoint version - The LED Driver is housed within the junction box. (L. 3.05" | W. 1.5" | H. .98")
- Pivots 88° and able to point straight down



## LAMPING

Includes field replaceable 14.2 watt, 634 delivered lumen, 2700K, 3000K or 3500K field replaceable LED module. Dimmable with most LED compatible ELV or Triac dimmers. Choice of 18° or 40° field changeable optics. Integrated lens holder accommodates up to two MR16 sized lenses or louvers (sold separately). As a general rule when using the Burk head, we do not recommend using greater than 70% of the maximum wattage specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support.

Aged Brass /  
Aged Brass



Antique Bronze /  
Antique Bronze

Black /  
Satin Nickel

Satin Nickel /  
Satin Nickel

White /  
Satin Nickel

To view all available finish options, please visit [techlighting.com](http://techlighting.com)

## ORDERING INFORMATION

| 700 | SYSTEM       | BRK | CRI      | COLOR TEMP | BEAM SPREAD | LENGTH (A) | FINISH                               | LAMP |
|-----|--------------|-----|----------|------------|-------------|------------|--------------------------------------|------|
|     | FJ FREEJACK  |     | 8 80 CRI | 27 2700K   | 20 18°      | 03 3"      | R AGED BRASS                         | LED  |
|     | MP MONOPOINT |     | 9 90 CRI | 30 3000K   | 35 40°      | 06 6"      | Z ANTIQUE BRONZE                     |      |
|     | MO MONORAIL  |     |          | 35 3500K   |             |            | B BLACK<br>S SATIN NICKEL<br>W WHITE |      |

Compatible with following accessories. 140MR16DF DIFFUSOR LENS MR16/PAR16 \*\*\* 140MR16LL LINEAR SPREAD LENS MR16/PAR16 \*\*\* 140MR16SB SANDBLASTED LENS MR16 \*\*\* 140MR16SF SOFT FOCUS LENS MR16/PAR16 \*\*\* 700A02-BK EGGCRATE MR16/PAR16 BLACK

700 \_\_\_\_\_ BRK \_\_\_\_\_


JOB NAME \_\_\_\_\_

NOTES \_\_\_\_\_



## SPECIFICATIONS

|                               |            |
|-------------------------------|------------|
| PRIMARY MATERIAL              | Metal      |
| SHADE MATERIAL                |            |
| NET WEIGHT                    | 2 lbs      |
| HEIGHT                        | 3in        |
| WIDTH                         | 3.6in      |
| LENGTH                        | 3in        |
| BEAM SPREAD                   |            |
| UP LIGHT / DOWN LIGHT / BOTH? |            |
| WET LISTED                    |            |
| DAMP LISTED                   |            |
| DRY LISTED                    |            |
| MIN. HANGING HEIGHT           | 3in        |
| MAX HANGING HEIGHT            | 3in        |
| TOTAL CORD LENGTH             |            |
| SLOPED CEILING ADAPTABLE?     | N/A        |
| GENERAL LISTING               | ETL Listed |
| INCLUDES                      |            |



## LAMPING SPECIFICATIONS

|                       | LED LAMP                      | INTEGRATED LED | NON LED | NO LAMP |
|-----------------------|-------------------------------|----------------|---------|---------|
| DELIVERED LUMENS      | 634.0                         |                |         |         |
| WATTS                 | 14.2                          |                |         |         |
| MAX WATTAGE PER BULB  | 14.2W                         |                |         |         |
|                       | 12V ELV, MLV<br>120V ELV, MLV |                |         |         |
| CCT                   | 2700K<br>3000K<br>3500K       |                |         |         |
| CRI                   | 80 CRI<br>90 CRI              |                |         |         |
| LED LIFETIME          |                               |                |         |         |
| L70                   | >50000                        |                |         |         |
| AVERAGE BULB HOURS    |                               |                |         |         |
| FIELD SERVICEABLE LED |                               |                |         |         |
| LAMP BASE             | Integrated LED                |                |         |         |
| LAMP SHAPE            | Integrated LED                |                |         |         |
| LAMP INCLUDED?        | True                          |                |         |         |
| WARRANTY**            | 5 Years                       |                |         |         |

\* Dimming information available at [www.techlighting.com/Downloads#dimming](http://www.techlighting.com/Downloads#dimming)

\*\* Visit [techlighting.com](http://techlighting.com) for specific warranty limitations and details.

## T20 / T24 / JA8 INFORMATION

|   | Integrated LED | Replacement LED Lamp | No Lamp * |
|---|----------------|----------------------|-----------|
| This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.                           |                | No                   |           |
| This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California. |                | N/A                  |           |

\* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.

