

MAGNETIC TRANSFORMER

OUTDOOR 150W/300W



High quality stainless steel construction
for quality protection against the elements

Features:

- Isolated output power per NEC and UL safety requirements
- Auto-reset; Short-circuit, Overload and Thermal protection
- Soft Start, Dimmable, and Outdoor grade material
- Timer and Photocell option inside housing

SPECIFICATIONS


INPUT VOLTAGE	120V: 120V AC 50/60Hz 277V: 277V AC 50/60Hz
INPUT CURRENT	120V: 1.25A (150W) 277V: 0.54A (150W) 120V: 2.5A (300W) 277V: 1.08A (300W)
OUTPUT VOLTAGE	120V: 12V AC 277V: 12V AC
OUTPUT CURRENT	120V: 12.5A 277V: 12.5A
MOUNTING OPTIONS	Wall (12" above finished grade)
DIMMING	Magnetic Low Voltage
EFFICIENCY	80%
POWER FACTOR	>98%
CAST TC*	90°C Max.
PROTECTION	Input/Output
STORAGE	-30°C/+90°C
HUMIDITY	95% RH Max
WET LISTED	IP 60, 67
WARRANTY*	5 Years



MAGNETIC TRANSFORMER
shown in stainless steel



MAGNETIC TRANSFORMER
shown in stainless steel



* Visit techlighting.com for specific warranty limitations and details.
As a general rule when using LED fixtures, we do not recommend using greater than 70% of specified maximum wattage on the transformer due to inrush current. For assistance, please contact our technical support department.

ORDERING INFORMATION

ITEM	DESCRIPTION	HOUSING	DIMMING
7000T150T	OTDR, MAGNETIC, 150W, 120V	STAINLESS STEEL	MAGNETIC
7000T150T277	OTDR, MAGNETIC, 150W, 277V	STAINLESS STEEL	MAGNETIC
7000T300T	OTDR, MAGNETIC, 300W, 120V	STAINLESS STEEL	MAGNETIC
7000T300T277	OTDR, MAGNETIC, 300W, 277V	STAINLESS STEEL	MAGNETIC

*OUTDOOR RATED, ORDERED SEPARATELY

PROJECT INFO

FIXTURE TYPE & QUANTITY	JOB NAME & INFO	NOTES



GENERATION BRANDS
7400 Linder Avenue, Skokie, Illinois 60077
T 847.410.4400 F 847.410.4500