

Phobos Pendant

700TDPHB_ 1.0

VISUAL COMFORT & Co.

MODERN COLLECTION

GENERAL PRODUCT INFORMATION:



This product is suitable for indoor locations.

Dimmable with most LED compatible ELV, TRIAC and 0-10V dimmers.


This instruction shows a typical installation.

CAUTION - RISK OF FIRE

This product must be installed in accordance with the applicable installation code by a person familiar with the construction and operation of the product and the hazards involved.


Use minimum 90°C supply conductors.

SAVE THESE INSTRUCTIONS!



Install the Fixture

1A



- 1 Install the mounting plate to the electrical box with the two provided #8-32 screws.
- 2 Determine the desired height of the fixture using the provided stems and half ball/upper stem and assemble them by screwing them together. Note: stem without a collar must be installed on the bottom of the assembly.
- 3 Slide the canopy, then the collar nut onto the half ball/stem assembly.
- 4 Feed the fixture wires through the stem assembly, then screw the stem assembly to the top of the socket.
- 5 Seat the half ball into the mounting plate ensuring no wires are being pinched.
- 6 Connect the negative (-) fixture wire to the negative (-) output driver wire with a wire nut.
- 7 Connect the positive (+) fixture wire to the positive (+) output driver wire with a wire nut.
- 8 Connect the fixture to a suitable ground in accordance with local electrical codes.
- 9 Connect the white input driver wire to the neutral power line wire with a wire nut.
- 10 Connect the black input driver wire to the hot power line wire with a wire nut.
- 11 Neatly place the driver, wire, and wire nut connections inside the canopy/electrical box, then slide the canopy up over the mounting plate and secure in place with the collar nut.
- 12 Install the diffuser by inserting them firmly into the socket.