BRIM HEAD

VISUAL COMFORT & CO.

PRODUCT FEATURES

- From the brand formerly known as Tech Lighting
- Field-changeable optics for ultimate customization
- Monopoint version The LED Driver is housed within the junction box. (L. 3.05" | W. 1.5" | H. .98")
- Modest size profile to minimize bulky appearance ٠
- Compatible with the Monorail and Monopoint systems by Tech Lighting

Includes 9.2 watt, 647.5 delivered lumens, 2700K or 3000K, 90 CRI field replaceable LED module Dimmable with most LED compatible ELV and Triac dimmers. Choice of 20°, 30° or 40° field changeable optics. Integrated lens holder accommodates up to 2 lenses or louvers (sold separately) As a general rule when using the Brim head, we do not

recommend using greater than 33% of the maximum wattage

specified for the low voltage transformer due to inrush current requirements. For assistance in calculations, please contact Technical Support. Brim head only compatible with AC transformers. Can use

٠ Available in modern finishes

I AMPING

MOCxx Lens.



Clear Black Finish



Clear Black Finish

Transparent Smoke Black Finish

Clear Satin Nickel Finish

Transparent Smoke Satin Nickel Finish

To view all available finish options, please visit techlighting.com

ORDERING INFORMATION

700	SYSTEM BR	M COLOR TEMP	BEAM SPREAD	LENGTH (A)	COLOR	FINISH
	FJ FREEJACK	927 90 CRI 2700K	20 20°	05 5"	CCLEAR	B MATTE BLACK
	MP MONOPOINT	930 90 CRI 3000K	30 30°	08 7.76"	K TRANSPARENT SMOKE	S SATIN NICKEL
	MO MONORAIL		40 40°	14 13.76"		

Note. MP includes 4 Round Flush Canopy.

Matte Black Finish option ships with Satin Nickel Stem.

4" Stem length not available on WMO System option. For custom stem lengths, please contact the Quotes Department.

700	BRM
JOB NAME	

NOTES

700



© 2019 Tech Lighting, L.L.C. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, L.L.C. Tech Lighting reserves the right to change specifications for product improvements without notification.


7400 Linder Avenue, Skokie, IL 60077 T 847.410.4400 | F 847.410.4500 | techlighting.com

BRIM HEAD

VISUAL COMFORT & CO.

SPECIFICATIONS

		(H)
PRIMARY MATERIAL	Metal	
SHADE MATERIAL		
NET WEIGHT	0.79 lbs	
HEIGHT	1.3in	
WIDTH	3in	
LENGTH	3in	
BEAM SPREAD		
UP LIGHT / DOWN LIGHT / BOTH?		
WET LISTED		
DAMP LISTED		
DRY LISTED		
MIN. HANGING HEIGHT	4.8in	
MAX HANGING HEIGHT	13.8in	
TOTAL CORD LENGTH		
SLOPED CEILING ADAPTABLE?	No	
GENERAL LISTING	ETL Listed	
INCLUDES		



LAMPING SPECIFICATIONS

	LED LAMP	INTEGRATED LED	NON LED	NO LAMP
DELIVERED LUMENS	647.5			
WATTS	9.2			
MAX WATTAGE PER BULB	9.2W			
	12V ELV			
	120V ELV			
ССТ	Clear, Transparent Smc	oke : 2700K		
	Clear, Transparent Smo	oke : 3000K		
CRI	90 CRI			
LED LIFETIME				
L70	>50000			
AVERAGE BULB HOURS	50000			
FIELD SERVICEABLE LED				
LAMP BASE	Integrated LED			
LAMP SHAPE	Integrated LED			
LAMP INCLUDED?	True			
WARRANTY**	5 Years			

* Dimming information available at <u>www.techlighting.com/Downloads#dimming</u> ** Visit techlighting.com for specific warranty limitations and details.

T20/T24/JA8 INFORMATION

	Integrated LED	Replacement LED Lamp	No Lamp *
This product can be used to comply with California Building Energy Efficiency Standards 2016 Title 24 Part 6 / JA8.		Yes	
This product can be used to comply with California Appliance Efficiency Standards 2016 Title 20 and may be shipped to and sold in California.		N/A	

* If a light fixture or component does not include a lamp or light source, it is the responsibility of the customer to select a lamp that meets the T24 and T20 requirements.



© 2019 Tech Lighting, LLC. All rights reserved. The "Tech Lighting" graphic is a registered trademark of Tech Lighting, LLC. Tech Lighting reserves the right to change specifications for product improvements without notification.