

# Candelabra (E12) Torpedo Clear


5 W / 500 LM / 3000K

SPECIFICATIONS

| PHYSICAL                                                                                                                                                 |                               |
|----------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|
| Diameter                                                                                                                                                 | 1.375"                        |
| Height                                                                                                                                                   | 4"                            |
| Glass Shape                                                                                                                                              | Torpedo                       |
| Base                                                                                                                                                     | Candelabra (E12)              |
| Materials                                                                                                                                                | Glass, Nickel                 |
| Glass Finish                                                                                                                                             | Clear                         |
| Weight                                                                                                                                                   | 0.05 lbs                      |
| Max Ambient Temp.                                                                                                                                        | 40°C                          |
| IP Rating                                                                                                                                                | IP65                          |
| ELECTRICAL                                                                                                                                               |                               |
| Power                                                                                                                                                    | 5 W                           |
| Current                                                                                                                                                  | 0.056 A                       |
| Voltage                                                                                                                                                  | 120 V                         |
| Frequency                                                                                                                                                | 60 Hz                         |
| Power Factor                                                                                                                                             | ≥0.9                          |
| Efficacy                                                                                                                                                 | 100 lm/W                      |
| Lifetime                                                                                                                                                 | 15000 hrs                     |
| Dimmability                                                                                                                                              | <3% (depending on the dimmer) |
| ILLUMINATION                                                                                                                                             |                               |
| CCT                                                                                                                                                      | 3000K                         |
| Lumens                                                                                                                                                   | 500 lm                        |
| Incandescent Equiv.                                                                                                                                      | 60 W                          |
| Flicker                                                                                                                                                  | Flicker Free                  |
| Beam Spread                                                                                                                                              | 320°                          |
| Light Source                                                                                                                                             | LED                           |
| CRI                                                                                                                                                      | ≥90                           |
| R9                                                                                                                                                       | ≥50                           |
| TM30 - Rg                                                                                                                                                | ≥90                           |
| TM30 - Rf                                                                                                                                                | ≥90                           |
| FEATURES                                                                                                                                                 |                               |
| This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability. |                               |
| WARRANTY                                                                                                                                                 |                               |
| 2 Years                                                                                                                                                  |                               |



POLAR DISTRIBUTION



ORDERING INFORMATION

| PACKAGE TYPE | PRODUCT SKU | QUANTITY |
|--------------|-------------|----------|
| INDIVIDUAL   | VB10006B    | 1        |
| MASTER PACK  | VB10006B    | 6        |

MULTIPACK: if 6 or more are ordered, the item will ship in a Master Pack

