

Candelabra (E12) G16-1/2 Clear


4 W / 350 LM / 2700K

SPECIFICATIONS

PHYSICAL	
Diameter	2"
Height	3"
Glass Shape	G16-1/2
Base	Candelabra (E12)
Materials	Glass, Nickel
Glass Finish	Clear
Weight	0.07 lbs
Max Ambient Temp.	40°C
IP Rating	IP65
ELECTRICAL	
Power	4 W
Current	0.045 A
Voltage	120 V
Frequency	60 Hz
Power Factor	≥0.9
Efficacy	87.5 lm/W
Lifetime	15000 hrs
Dimmability	<3% (depending on the dimmer)
ILLUMINATION	
CCT	2700K
Lumens	350 lm
Incandescent Equiv.	40 W
Flicker	Flicker Free
Beam Spread	320°
Light Source	LED
CRI	≥90
R9	≥50
TM30 - Rg	≥90
TM30 - Rf	≥90
FEATURES	
This advanced LED technology is carefully designed and selected to consist of the highest quality LED chipsets for superior performance and reliability.	
WARRANTY	
2 Years	



POLAR DISTRIBUTION



ORDERING INFORMATION

PACKAGE TYPE	PRODUCT SKU	QUANTITY
INDIVIDUAL	VB10011A	1
MASTER PACK	VB10011A	6

MULTIPACK: if 6 or more are ordered, the item will ship in a Master Pack

