

V9646-5

2-Light Integrated LED Indoor or Outdoor Black Aluminum Cylinder Wall Mount or Wall Sconce

Catalog #:

Type: Project:

Prepared By:

Because Lighting Speaks Volumes

Description

This sleek, modern integrated LED indoor or outdoor (suitable for wet locations with top cover only [included with purchase]) black aluminum cylinder wall mount or wall sconce features a professional look and formed and welded, all-aluminum construction. Feel at ease with aluminum's corrosion-resistance, high resilience, lasting quality, and inability to rust like steel. Powder-coated paint base finish provides phenomenal long-lasting color and exceptional corrosion/scratch resistance. Go green and save big. Energy-efficient LEDs are environmentally friendly and require substantially less electricity to maintain, passing down cost-cutting savings to you. Feel confident in your choice of elegant simplicity. Delight in clean, minimal, and solid color design that blends in seamlessly with surroundings and existing décor. Offers remarkable versatility for exterior and interior design. A stunning piece that imparts a fresh, rejuvenating, and open atmosphere both outside and within. Change up your exterior spaces with this look, or be unique—bring the outdoor look indoors. Open/uncovered bottom helps prevent accumulation of dust or pests. Perfect complement to indoor or outdoor (suitable for wet locations with top cover only [included with purchase]) spaces. Flawlessly and evenly finished in solid black. Feel confident in a quality product. Each integrated LED comes with a 5-year limited warranty. Modernize your spaces with this smart, bold piece.

Specifications

Style	Modern
Type of Lighting	Indoor or Outdoor Wall Lighting
Product Type	Wall Mount
Product Subtype	Sconce
Height (in.)	18
Width (in.)	6
Length or Extension/Projection (in.)	8.75
Finish	Black
Main Material	Formed & Welded, Powder-Coated All- Aluminum
Other Material	Black Powder- Coated Aluminum Cylinder (Includes Top Cover with Clear Glass)

Light Direction	Up and Down (One Uplight [Clear Glass Top Cover] and One Downlight)
Installation/Mounting Position	Downward Only (Top of Cylinder Has Cover with Clear Glass) (Bottom of Cylinder is Open/ Uncovered)
Mounting Deck Height (in.)	5
Mounting Deck Width (in.)	5
Mounting Deck Shape	Square
Installation Location	Wet (With Top Cover Only) (Top Cover [Included with Purchase] Contains Clear Glass for Uplight)
Light #	2
Watts per Light (W)	15
Total Wattage (W)	30
Light Source Included?	Yes (Integrated LEDs)
Light Bulb(s) Included?	N/A (Integrated LEDs Included as Light Source)
CRI	80
Color Temperature (K)	3000
Lumens per Light	1000
Total Lumens	2000
Output Power Supply	Class II
Output Power Supply Power Factor (Pf)	Class II >.9
Power Factor (Pf)	>.9
Power Factor (Pf) THD	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values
Power Factor (Pf) THD Life Rated (Hours)	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V
Power Factor (Pf) THD Life Rated (Hours) Dimmable?	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V Only])
Power Factor (Pf) THD Life Rated (Hours) Dimmable? Base	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V Only]) N/A (Integrated LED)
Power Factor (Pf) THD Life Rated (Hours) Dimmable? Base Input Voltage (Volts)	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V Only]) N/A (Integrated LED) 120V at 50/60 Hz ROHS Compliant
Power Factor (Pf) THD Life Rated (Hours) Dimmable? Base Input Voltage (Volts) Compliances	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V Only]) N/A (Integrated LED) 120V at 50/60 Hz ROHS Compliant FCC Compliant
Power Factor (Pf) THD Life Rated (Hours) Dimmable? Base Input Voltage (Volts) Compliances Safety Ratings	>.9 <20% 50,000 (Based on LED Testing per LM80-08 and Projected Values from IESNA TM21-11) Yes (Flicker-Free TRIAC/ELV, 5% [120V Only]) N/A (Integrated LED) 120V at 50/60 Hz RoHS Compliant FCC Compliant cULus Listed No Assembly



Surface Wall Mount E: 8¾" I: 18 III

At a Glance

- Sturdy, Exquisite Construction
- 5-Year Limited Warranty on Integrated LEDs (Included with Purchase)
- Powder-Coated Aluminum Cylinder (Top Cover Includes Clear Glass)
- Perfect Complement to Indoor or Outdoor (With Top Cover Only, Included with Purchase) Spaces
- Black Finish
- High-Quality, Corrosion-Resistant, and Rust-Resistant All-Aluminum
- Powder-Coated Hard Surface Provides Long-Lasting Color and Corrosion/Scratch Resistance
- Modern Design
- Go Green—Environmentally Friendly, Energy-Efficient Integrated LEDs
- Mounts Down Only (Included Top Cover Contains Clear Glass) (Bottom is Open/Uncovered)
- Clean, Minimal, and Solid Color Design Blends in Seamlessly with Surroundings and Existing Décor
- Open/Uncovered Bottom Helps Prevent Accumulation of Dust or Pests
- 1000 Lumens per LED (2000 Lumens Total)
- 3000K Color Temperature
- 80 CRI
- Dimmable (Flicker-Free TRIAC/ELV, 5% [120V Only])
- Enjoy Rain or Shine—Conveniently Suitable for Wet Locations (With Top Cover Only)
- Heat-Resistant Components Withstand Up to 15 Watts
- 2-Light Fixture (Integrated LEDs Included)
- Individually Inspected for Quality Assurance
- cULus Listed for Safety