
HR-LED90

HR90 LED Button Light

WAC LIGHTING

Responsible Lighting®



Fixture Type:	
Catalog Numbe	er:
Project:	
Project.	
Location:	

PRODUCT DESCRIPTION

Designed for recessed or surface mounted installations, delivering strong light output with the latest in LED technology.

FEATURES

- Meets 2013 California Title 24 Efficiency
- High CRI: 90+
- Recessed or surface mounting options
- Quick and easy installation
- Includes 72" pre-installed lead wire
- 100,000 hour rated life
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Die-cast aluminum fixture, stamped steel housing for surface mount. Beam spread lens.

Power: Class 2, 24V remote and plug-in transformers allow for up to 10 button lights to be wired together. Use a multiple terminal block to wire up to 6 fixtures in a neat under cabinet installation without the use of open splices (see below).

Light Source: 2700K or 3000K mid-power LEDs. CRI 90

Dimming: May be dimmed down to 5% with an electronic low voltage (ELV) dimmer. Compatible with LUTRON DVELV-300 and SELV-300 (ELV) dimmer.

Mounting: *Recessed*–3½" cutout hole. Compression springs hold fixture firmly in place. *Surface*–Screw mounting plate to surface, snap the fixture onto the mounting plate. *Not recommended for use in ceiling.*

Finish: Black (BK), Brushed Nickel (BN) and White (WT).

Standards: ETL and cETL Listed. Energy Star Rated. CEC Title 24 Compliant

ORDER NUMBER


	Cold	or Temp	Finis	sh	Power	Lumens
HR-LED90	27 30	2700K 3000K	BK WT BN	Black White Brushed Nickel	5W*	200

*Power consumption may vary depending on the efficiency of the power supply being used.



Example: HR-LED90-27-BK

- · Minimizes wiring back to transformer
- No voltage drop, power supplied using a variable current
- · If one fixture goes out the rest remain on



FINISHES

ВK





CLASS 2 ELECTRONIC TRANSFORMERS

Туре	Model	Dim	Input	Output	Power Up To	Dimensions
Domete	EN-2460-RB2	Yes	1201/	24V AC/60W	7 × LED90	6½" × 15%" × 1¼"
Remote EN-	EN-24100-RB2			24V AC/96W	10 × LED90	6½" × 15%" × 1¼"
Plug-In	EN-2460-P-AR	Yes	120V	24V AC/60W	7×LED90	2¾" X 15%" X 1¾"

Includes 6' cord and 5 SL-WC-1 clips.

MULTIPLE TERMINAL BLOCK

Model #	Dimensions					
MTB-01	L: 3¼"	W: 1¾"	H: 7⁄8"			

12.5A max accommodates up to 6 output connections for 14 AWG wires.

WAC Lighting
www.waclighting.com
Phone (800) 526.2588 • Fax (800) 526.2585

Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 Western Distribution Center 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585