1" INGROUND - SLIM ROUND

1011



LANDSCAPE LIGHTING



Fixture Type:	
Catalog Numbe	er:
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape 1" recessed inground luminaire for soft ground application.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Rated Life:

70,000 hours

ORDERING NUMBER

	Color Temp	Finish
1011 Slim round	30 3000K	SS Stainless Steel

1011-30SS

1" INGROUND - ROUND

1021



LANDSCAPE LIGHTING



Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

PRODUCT DESCRIPTION

Landscape 1" recessed inground luminaire for up, down, side light applications.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

	Color Temp	Finish	
1021 Round	30 3000K	SS St	tainless Steel

1021-30SS

ACCESSORIES

1" Concrete Pour Adapter



1000-CON-PVC

For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 1" schedule 80 PVC pipe

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

SPECIFICATIONS

Brightness: 80 lm **Beam Angle:** 50°

9 - 15VAC 1.9W / 3VA

70,000 hours

85

Input:

Power:

CRI:

Rated Life:

1" INGROUND - SQUARE


1051



LANDSCAPE LIGHTING







Fixture Type:		
Catalog Numbe	r:	
Project:		
Location:		

PRODUCT DESCRIPTION

Landscape 1" recessed inground luminaire for up, down, side light applications.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

	Color Temp	Finish
1051 Square	30 3000K	SS Stainless Steel

SPECIFICATIONS

 Input:
 9 - 15VAC

 Power:
 1.9W / 3VA

 Brightness:
 80 lm

 Beam Angle:
 50°

 CRI:
 85

Rated Life: 70,000 hours

1051-30SS

ACCESSORIES

1" Concrete Pour Adapter



1000-CON-PVC

For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 1" schedule 80 PVC pipe

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

2" INGROUND - SLIM ROUND






LANDSCAPE LIGHTING







Fixture Type:		
Catalog Number:		
Project:		

PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for soft ground application.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Location:

 Input:
 9 - 15VAC

 Power:
 4.1W / 6.6VA

 Brightness:
 170 lm

 Beam Angle:
 25°

 CRI:
 85

Rated Life: 70,000 hours

ORDERING NUMBER

	Colo	r Temp	Finish	
2011 Slim round	30	3000K	BS SS	Bronzed Stainless Steel Stainless Steel

2011-30____

Example: 2011-30SS

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

2" INGROUND - ROUND

2021



LANDSCAPE LIGHTING



Fixture Type:		
Catalog Numbe	r:	
Project:		
Location:		

PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for up, down, side light applications.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring, and 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

		Color Temp		Finish	
2021 R	ound	30	3000K	BS SS	Bronzed Stainless Steel Stainless Steel

2021-30____

Example: 2021-30SS

ACCESSORIES

2" Concrete Pour Adapter



2000-CON-PVC

For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 2" schedule 80 PVC pipe

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

SPECIFICATIONS

Brightness: 170 lm **Beam Angle:** 25°

9 - 15VAC 4.1W / 6.6VA

70,000 hours

85

Input:

Power:

CRI:

Rated Life:

2" INGROUND - SQUARE

2051



LANDSCAPE LIGHTING





Fixture Type:		
Catalog Numbe	r:	
Project:		
Location:		

PRODUCT DESCRIPTION

Landscape 2" recessed inground luminaire for up, down, side light applications.

FEATURES

- IP68 rated, Suitable for continuous immersion under water
- Factory sealed water tight fixtures
- Solid stainless steel construction
- Stainless steel spring clip allows wall or downlight applications
- Available Concrete Pour Adapter
- Spring clip, 6' lead wire and direct burial gel filled wire nuts included
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

ORDERING NUMBER

		Color	Temp	Finish		
2051	Square	30	3000K	BS SS	Bronzed Stainless Steel Stainless Steel	

2051-30____

Example: 2051-30SS

ACCESSORIES

2" Concrete Pour Adapter



2000-CON-PVC

For installation in concrete. Use with a 4" outdoor rated junction box and a trade size 2" schedule 80 PVC pipe

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122

SPECIFICATIONS

Brightness: 170 lm **Beam Angle:** 25°

9 - 15VAC

85

4.1W / 6.6VA

70,000 hours

Input:

Power:

CRI:

Rated Life: