INVISIBLE TRIM HOUSING

4.5" Volta

WAC LIGHTING

Responsible Lighting®

Input: Universal 120 - 277V AC 50/60 Hz

Standards: ETL & cETL, Chicago Plenum, IC-rated, Airtight (see below for list)

Dimming: Electronic Low Voltage (ELV): 100%-5% (120V only)

0-10V: 100%-0% (120 - 277V)

Emergency: EM fixtures provided with integral Emergency battery back up with

24" lead wire remote test switch. Provides at least 90 minutes of 5W

illumination during emergency operation.

Mounting: New construction housings included with

universal mounting brackets and hanger bars

Ceiling cut out (Round): Ø 5 1/8" Ceiling cut out (Square): 5 1/8" x 5 1/8" See next page for ceiling thickness information

Construction: 20 Gauge cold rolled steel

Diecast spackle flange included

Warranty 5 year WAC Lighting product warranty

Fixture Type:


Catalog Number:


Project:

Location:

Round New Contruction









Square New Construction







HOUSINGS

	Model		Power*	S	N, F,W, A	Rating	Emergency Back	kup Compatible Trims
Round New Contruction	R4RNL R4RCL	Airtight Airtight, Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM Emergence backup battery (OPTIONA	R4RD1L R4RAL
Sauare New Construction	R4SNL R4SCL	Airtight Airtight, Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM Emergence backup battery (OPTIONA	R4SD1L R4SAL

^{*}Power consumption depends on beam angle of the trim.

R4_____-Example: R4RNL-15 or R4RNL-15EM (with Emergency backup battery) Field Replaceable Driver

D-R4	N-15	Driver for 15W New Construction Hsg
D-R4	N-25	Driver for 25W New Construction Hsg
D-R4	N-36	Driver for 36W New Construction Hsg

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

INVISIBLE TRIM HOUSING

4.5" Volta

WAC LIGHTING

Responsible Lighting®

CEILING THICKNESS BY TRIM

		Ceiling Thickness				
Trim Model	Trim Description	1/2"	1"	1 1/2"		
R4RD2L R4SD2L	Downlight	Yes	Yes	Yes		
R4RD1L R4SD1L	Shallow Regressed Downlight	Yes	Yes	Yes		
R4RAL R4SAL	Adjustable	Yes, to 45°	Yes, to 45°	Yes, to 35°		
R4RWL R4SWL	Wall Wash	Yes	Yes	No		