R4RAT, R4SAT

4.5" Volta - Adjustable

WAC LIGHTING

Responsible Lighting®



Shown Trimless For reference

Fixture Type:	
Catalag Numba	
Catalog Number	:
Project:	
Location:	

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for the architectural lighting industry. This high lumen family of fixtures, with an extensive set of round and square fittings enables lighting designers an advanced system for a clean, uncluttered ceiling

FEATURES

- Dual finishes are single piece, no physical seams
- · Center beam alignment retained throughout adjustment range
- 0-45° vertical and 365° horizontal lockable hot aiming
- Compatible with wide range of accessories

SPECIFICATIONS

Construction: Durable die-cast self flanged aluminum construction

Input: 120 - 277VAC

Dimming: Electronic Low Voltage (ELV): 100%-5%

0-10V: 100%-0%

Mounting: Two heavy gauge retention clips hold trim firmly

Accomodates 1/2 "- 1 1/2" ceiling thickness

Finish: Powder coated white, black and haze

Standards: ETL & cETL Wet location Listed

TRIMS (ORDER HOUSING SEPARATELY)

			Reference	e Output*					
Model		Beam Angle	Lumens	CBCP	Color Temp	CRI	Finishes	Reflector/Trim	
67/8" max	R4RAT Round	S 15° N 25° F 45°	1251 2366 2201	11865 7173 3947	827 2700K 927 2700K 830 3000K 930 3000K 835 3500K 840 4000K	85 90 85 90 85 85	BK BKWT HZ HZWT WT	Black Black/White Haze Haze/White White	
Trim -4½"5¾"	R4SAT Square	S 15° N 25° F 45°	1208 1653 1342	12465 8308 2313	827 2700K 927 2700K 830 3000K 930 3000K 835 3500K 840 4000K	85 90 85 90 85 85	BK BKWT HZ HZWT WT	Black Black/White Haze Haze/White White	

^{*}Reference output shows 830(80CRI 3000K) trim with 36 housing. Use multiplier table below to determine the output for other combinations.

Multiplier		TRIM							
		827	927	830	930	835	840		
HOUSING	36	0.937	0.764	1.000	0.815	1.045	1.054		
	25	0.685	0.558	0.731	0.596	0.764	0.770		
	15	0.456	0.371	0.486	0.396	0.508	0.512		

R4__AT-____-

Example: R4RAT-S827-HZWT

Please see next page for housing units(required)

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 **Headquarters/Eastern Distribution Center** 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

R4RAT, R4SAT

4.5" Volta - Adjustable

WAC LIGHTING

Responsible Lighting®


HOUSINGS (REQUIRED)

			Model		S	N, F	Rating	Options	
New Contruction, Airtight 65%" 38"	131/16" (EM option)	R4RNT R4RCT	Round Round Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM	Emergency backup battery (Optional)
New Contruction, Airtight 65/8" 3/8" 1711/16" 223/16"	131/16" (EM option)	R4SNT R4SCT	Square Square Chicago Plenum	15 25 36	10W 15W 23W	15W 25W 36W	IC rated IC rated Non-IC	EM	Emergency backup battery (Optional)
Remodel 13/4" 1	37/6" 24" max	R4BRT	Round or Square	15 25 36	10W 15W 23W	15W 25W 36W	Non-IC Non-IC Non-IC		N/A

^{*}Power consumption depends on beam angle of the trim.

R4 -

Example: R4RNT-15 or R4RNT-15EM (with Emergency backup battery)



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760


R4RAT, R4SAT

4.5" Volta - Adjustable

WAC LIGHTING

Responsible Lighting®

FIELD CHANGEABLE AIMING



0 - 45° vertical lockable hot aiming



365° horizontal lockable hot aiming