

R4RWL, R4SWL

4.5" Volta - Wallwash Invisible Trim

WAC LIGHTING

Responsible Lighting®

Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Volta LED downlight series represents an innovation in design and technology for the architectural lighting industry. This high lumen family of fixtures, with an extensive set of round and square fittings enables lighting designers an advanced system for a clean, uncluttered ceiling

FEATURES

- Dual finishes are single piece, no physical seams
- Innovative bi-directional spread lens
- Engineered for even wall illumination both vertically and horizontally
- Compatible with wide range of accessories

SPECIFICATIONS

Construction: Durable die-cast self flanged aluminum construction

Input: 120 - 277VAC


Dimming: Electronic Low Voltage (ELV): 100%-5%
0-10V: 100%-0%

Mounting: Two heavy gauge retention clips hold trim firmly
Accommodates 1/2" - 1 1/2" ceiling thickness

Finish: Powder coated white, black and haze

Standards: ETL & cETL Wet location Listed

TRIMS (ORDER HOUSING SEPARATELY)

Model	Beam Angle	Reference Output*		Color Temp	CRI	Finishes	Reflector/Trim
		Lumens	CBCP				
 R4RWL Round	A Asym	1970	1493	827 2700K	85	BK HZ WT	Black Haze White
				927 2700K	90		
				830 3000K	85		
				930 3000K	90		
				835 3500K	85		
				840 4000K	85		
R4SWL Square	A Asym	2140	1352	827 2700K	85	BK HZ WT	Black Haze White
				927 2700K	90		
				830 3000K	85		
				930 3000K	90		
				835 3500K	85		
				840 4000K	85		

*Reference output shows 830(80CRI 3000K) trim with 36 housing. Use multiplier table below to determine the output for other combinations.

Multiplier	TRIM					
	827	927	830	930	835	840
HOUSING 36	0.937	0.764	1.000	0.815	1.045	1.054
HOUSING 25	0.685	0.558	0.731	0.596	0.764	0.770
HOUSING 15	0.456	0.371	0.486	0.396	0.508	0.512

R4_WL-_____-_____

Example: R4RWL-S827-WT

Please see next page for housing units(required)

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

R4RWL, R4SWL

4.5" Volta - Wallwash Invisible Trim

WAC LIGHTING

Responsible Lighting®

HOUSINGS (REQUIRED)


		Model	Power* A	Rating	Options
	R4RNL Round	R4RCL Round Chicago Plenum	15 15W	IC rated IC rated Non-IC	EM Emergency backup battery (Optional)
	R4RCL Round Chicago Plenum		25 25W		
	R4SNL Square	R4SCL Square Chicago Plenum	15 15W	IC rated IC rated Non-IC	EM Emergency backup battery (Optional)
	R4SCL Square Chicago Plenum		25 25W		

*Power consumption depends on beam angle of the trim.

R4 _____ - _____

Example: **R4RNL-15** or **R4RNL-15EM** (with Emergency backup battery)

BI-DIRECTIONAL SPREAD LENS



waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760