# **2" OCULUX -** Adjustable R2BRA, R2BSA

# WAC LIGHTING

Responsible Lighting®

|--|



Fixture Type:	
Catalog Number:	
Project:	

Location:

#### PRODUCT DESCRIPTION

Designed to fit in tight plenum space

#### FEATURES

- Energy Star<sup>®</sup> Rated
- Title 24 Compliant
- Cutout: 31/16"
- Single spot light source
- Sold as new construction, may be reconfigured in the field for remodel
- ELV or TRIAC or 0-10V dimming compatible

#### SPECIFICATIONS

Construction: Die-cast aluminum trim with aluminum heat sink Dimming: 100% - 5% with 0-10V dimmer 100% - 5% with Electronic Low Voltage (ELV) dimmer Input: 120V AC Power: 9W, power factor 0.98 Finish: Powder coated Standards: ETL & cETL Listed, damp location listed trims IC-rated airtight housing Ceiling thickness: ½" - 1"

Operating Temperature: -4°F to 104°F (20°C to 40°C)

RIM (SEE NEXT PAG	E FOR HOUSING)	Beam	Color	Temp	CRI	Lumen	CBCP	Finish	Interior/Trim
		<b>S</b> 15°	927 930	2700K 3000K	90 90	535 555	3131 3245	BN WT	Brushed Nickel White
R2BRA Round 0 - 35° Adjustable 45° visual cutoff 3% <sub>16</sub> " 5½"	6" <b>N</b> 25°	927 930	2700K 3000K	90 90	635 680	1984 2123	BN WT	Brushed Nickel White	
	<b>F</b> 45°	927 930	2700K 3000K	90 90	640 685	1053 1127	BN WT	Brushed Nickel White	
		<b>S</b> 15°	927 930	2700K 3000K	90 90	535 555	3131 3245	BN WT	Brushed Nickel White
R2BSA Square $1 \\ 0 - 35^{\circ}$ Adjustable $45^{\circ}$ visual cutoff $2 \\ 39 \\ 16^{\circ}$ $2 \\ 5 \\ 2''$	" <b>N</b> 25°	927 930	2700K 3000K	90 90	635 680	1984 2123	BN WT	Brushed Nickel White	
	<b>F</b> 45°	927 930	2700K 3000K	90 90	640 685	1053 1127	BN WT	Brushed Nickel White	

### R2BSA-\_\_


Example: R2BSA-N930-BN

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.

## INTEGRAL HOUSING AND TRIM: BOTH NEW CONSTRUCTION & REMODEL

**NEW CONSTRUCTION CONFIGURATION** *IC-Rated, Airtight* 



REMODEL CONFIGURATION IC-Rated, Airtight



waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program.