
TUBE ARCHITECTURAL DS-WS05

WAC LIGHTING

LED Wall Mounts

Responsible Lighting®





PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight[™] iOS App
- · High performance LED wall mounted light
- · Solid die cast aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277V, 50/60Hz

Controls: DMX512-A, Bluetooth v4.0. Configured with ilumenight[™] iOS App

Dimming: 100%-1% in CCT & Color via DMX or Bluetooth control **Light Source:** High output 2 Step Mac AdamEllipse LEDs, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

	Diameter	Power	Beam	Delivered Lumens @ 3000K	CBCP @ 3000K	Light Direction	Color Temp	Finish
Single			S 15° N 25° F 33°	745 645 620	6186 1951 1386	s Straight up or down		BK Black
	DS-WS05 5	" 31W	F	840	-	A Away from the wall	cc Color Changing	WT White BZ Bronze GH Graphite
				840		B Towards the wall		

DS-WS05-__-CC-___

Example: DS-WS05-FA-CC-GH




TUBE ARCHITECTURAL DS-WD05

WAC LIGHTING

Color Changing LED Wall Mounts

Responsible Lighting®



Fixture Type:	
Catalog Number:	
Project:	
Location:	

PRODUCT DESCRIPTION

The latest LED, Bluetooth, and DMX technology for precise color selection in an appealing cylindrical profile. Perfect for accent and wall wash lighting. Available in various light distribution and beam angle options.

FEATURES

- Full color gamut control through gradients of saturated colors from 1-100%
- Tunable White (CCT) Range: 1650-8000K
- Bluetooth control via ilumenight™ iOS App
- · High performance LED wall mounted light
- · Solid die cast aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277V, 50/60Hz

Controls: DMX512-A, Bluetooth v4.0. Configured with ilumenight™ iOS App

Dimming: 100%-1% in CCT & Color via DMX or Bluetooth control **Light Source:** High output 2 Step MacAdam Ellipse LEDs, 90+ CRI

Rated life of 50,000 hours at L70

Finish: Electrostatically powder coated white, black, bronze and graphite

Standards: IP65 rated, ETL & cETL wet location listed

Operating

Temperature: -40°F to 104°F (-40°C to 40°C)

Diameter	Power	Beam	Delivered Lumens @ 3000K	CBCP @ 3000K	Light Direction		Color Temp		Finish		
		S 15° N 25° F 33°	645 x2	6186 x2 1951 x2 1386 x2	s Straight up or						
Double DS-WD05 5"	31W x2	F	840 x2	-	A	Away from the wall		- CC Color Changin	Color Changing	BK WT	Black White
Double D3-WD03 3	31W X2				В	Towards the wall			Color Changing		Bronze Graphite
					С	One side each					

DS-WD05-__-CC-__

Example: DS-WD05-FA-CC-GH

