


HR2LEDT409P

2" Tesla™ Pro LED 30°-45° Adjustable Trim

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, round 30° to 45° adjustable trim with interior open reflector.

FEATURES

- 2" aperture
- Energy Star® rated (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+


Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® qualifying products.

TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR2LEDT409P 30°-45° Adjustable	N 27°	827 2700K	85	635	2053	Yes	BN Brushed Nickel CB Copper Bronze WT White 
		927 2700K	90	515	1598	No	
		830 3000K	85	665	2151	Yes	
		930 3000K	90	595	1849	No	
		835 3500K	85	715	2272	Yes	
		840 4000K	85	730	2294	Yes	
	F 40°	827 2700K	85	620	1243	Yes	
		927 2700K	90	490	982	No	
		830 3000K	85	630	1298	Yes	
		930 3000K	90	565	1104	Yes	
		835 3500K	85	680	1376	Yes	
		840 4000K	85	695	1395	Yes	

HR2LEDT409P

Example: HR2LEDT409PF835CB

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

REPLACEMENT MODULES

New Construction

HR-2LED-H09D-ICA IC-Rated, Airtight 120V-277V	HR-2LED-H09D-ICAC IC-Rated, Airtight Chicago Plenum 120V-277V
--	---

Reflectors

Narrow Flood Flood	SL-REF-BL10-1-N SL-REF-BL10-1-F
-----------------------	--

Remodel

HR-2LED-R14D Non-IC 120V-277V
--

LED

2700K	85 CRI	BXRC-27E1000-B-03
2700K	90 CRI	BXRC-27G1000-B-03
3000K	85 CRI	BXRC-30E1000-B-03
3000K	90 CRI	BXRC-30G1000-B-03
3500K	85 CRI	BXRC-35E1000-B-03
4000K	85 CRI	BXRC-40E1000-B-03

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760