


HR2LEDT509P

2" Tesla™ Pro LED Square 0-30° Adjustable

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

Minimum profile, square 0° to 30° adjustable trim with interior open reflector.

FEATURES

- 2" aperture
- Energy Star® rated
- CEC Title 24 Compliant (see below for list of models)
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

SPECIFICATIONS

Construction: Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

Light Source: Utilizes one 14.5W LED, CRI: 85 & 90+

Dimming: 0-10V Dimming: 100%-10%
ELV Dimming: 100%-15% (120V only)

Mounting: Two heavy gauge retention clips hold trim firmly to housing

Finish: White (WT) powder coat paint and electroplated Brushed Nickel (BN) and Copper Bronze (CB).

Standards: ETL & cETL Listed. See table below for Energy Star® and 2013 California Title 24 qualifying products.

TRIMS

| Model# | Beam | Color Temp | CRI | Lumens | CBCP | Energy Star® | 2013 Title 24 | Finish |
|----------------------------------|-------|------------|-----|--------|------|--------------|---------------|--|
| HR2LEDT509P 0°-30° Adjustable | N 30° | 827 2700K | 85 | 795 | 1870 | Yes | No | BN Brushed Nickel CB Copper Bronze WT White |
| | | 927 2700K | 90 | 645 | 1504 | Yes | Yes | |
| | | 830 3000K | 85 | 820 | 1895 | Yes | No | |
| | | 930 3000K | 90 | 740 | 1801 | Yes | Yes | |
| | | 835 3500K | 85 | 895 | 2075 | Yes | No | |
| | | 840 4000K | 85 | 910 | 2164 | Yes | No | |
| | F 45° | 827 2700K | 85 | 765 | 1066 | Yes | No | |
| | | 927 2700K | 90 | 620 | 876 | Yes | No | |
| | | 830 3000K | 85 | 800 | 1099 | Yes | No | |
| | | 930 3000K | 90 | 705 | 988 | Yes | Yes | |
| | | 835 3500K | 85 | 860 | 1205 | Yes | No | |
| | | 840 4000K | 85 | 870 | 1226 | Yes | No | |

HR2LEDT509P

Example: HR2LEDT509PF835BN

COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

New Construction

| | |
|--|---|
| HR-2LED-H09D-ICA IC-Rated, Airtight 120V-277V | HR-2LED-H09D-ICAC IC-Rated, Airtight Chicago Plenum 120V-277V |
|--|---|

Remodel

| |
|--|
| HR-2LED-R14D Non-IC 120V-277V |
|--|

REPLACEMENT MODULES

Reflectors

| | |
|-----------------------|--|
| Narrow Flood Flood | SL-REF-BL10-1-N SL-REF-BL10-1-F |
|-----------------------|--|

LED

| | | |
|-------|--------|--------------------------|
| 2700K | 85 CRI | BXRC-27E1000-B-03 |
| 2700K | 90 CRI | BXRC-27G1000-B-03 |
| 3000K | 85 CRI | BXRC-30E1000-B-03 |
| 3000K | 90 CRI | BXRC-30G1000-B-03 |
| 3500K | 85 CRI | BXRC-35E1000-B-03 |
| 4000K | 85 CRI | BXRC-40E1000-B-03 |

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760