


# HR3LEDT318P

3.5" Tesla™ Pro LED 0°-30° Adjustable Trim

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project:

Location:

## PRODUCT DESCRIPTION

Minimum profile, round 0° to 30° adjustable trim with interior open reflector.

## FEATURES

- 3.5" aperture
- Energy Star® rated
- Damp location listed
- 30° visual cutoff angle for glare control
- Adjustable fixtures are ideal for sloped ceiling applications
- 5 year WAC Lighting product warranty

## SPECIFICATIONS

**Construction:** Durable die-cast aluminum construction with borosilicate glass lens. Extruded aluminum heat sink.

**Power Consumption:** 21.5W

**Dimming:** 0-10V Dimming: 100%-10%  
ELV Dimming: 100%-15% (120V only)

**Mounting:** Two heavy gauge retention clips hold trim firmly to housing.

**Finish:** Powder coated white  
Electroplated brushed nickel and copper bronze

**Standards:** ETL & cETL Listed. See table below for Energy Star® qualifying products.

## TRIMS

Model#	Beam	Color Temp	CRI	Lumens	CBCP	Energy Star®	Finish
HR3LEDT318P 0° to 30° Adjustable	N 30°	827 2700K	85	1180	2472	Yes	<b>HBN</b> Haze/Brushed Nickel <b>HCB</b> Haze/Copper Bronze <b>HWT</b> Haze/White <b>BBN</b> Specular Black/Brushed Nickel <b>BCB</b> Specular Black/Copper Bronze <b>BWT</b> Specular Black/White <b>BN</b> Brushed Nickel <b>CB</b> Copper Bronze <b>WT</b> White
		927 2700K	90	990	2104	Yes	
		830 3000K	85	1225	2555	Yes	
		930 3000K	90	1115	2387	Yes	
		835 3500K	85	1330	2811	Yes	
	840 4000K	85	1335	2809	Yes		
	F 55°	827 2700K	85	1145	1364	Yes	
		927 2700K	90	970	1165	Yes	
		830 3000K	85	1195	1428	Yes	
		930 3000K	90	1085	1302	Yes	
835 3500K		85	1290	1548	Yes		
840 4000K	85	1310	1574	Yes			

**HR3LEDT318P**

Example: HR3LEDT318PF835BN

## COMPATIBLE HOUSINGS See individual housing spec sheets for complete information.

### New Construction

<b>HR-3LED-H18D1-ICAC</b> Narrow, IC-Rated, Airtight	120V-277V	<b>HR-3LED-H18D1-ICAC</b> Narrow, IC-Rated, Airtight Chicago Plenum	120V-277V
<b>HR-3LED-H18D-ICAC</b> IC-Rated, Airtight	120V-277V	<b>HR-3LED-H18D-ICAC</b> IC-Rated, Airtight Chicago Plenum	120V-277V
<b>HR-3LED-H18D-EMICA</b> IC-Rated, Airtight Emergency Backup Battery	120V	<b>HR3LED-H18D-EMICAF</b> IC-Rated, Airtight Emergency Backup Battery	277V

### Remodel

<b>HR-3LED-R22D</b> Non-IC	120V-277V
-------------------------------	-----------

## REPLACEMENT MODULES

### Reflectors

Narrow Flood	<b>SL-REF-BL10-1-N</b>
Flood	<b>SL-REF-BL10-1-F</b>

### LED

2700K	85 CRI	<b>BXRC-27E1000-B-03</b>
2700K	90 CRI	<b>BXRC-27G1000-B-03</b>
3000K	85 CRI	<b>BXRC-30E1000-B-03</b>
3000K	90 CRI	<b>BXRC-30G1000-B-03</b>
3500K	85 CRI	<b>BXRC-35E1000-B-03</b>
4000K	85 CRI	<b>BXRC-40E1000-B-03</b>

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760