MT-3LD111 - 1 Light

Mini LED Multiple Spots



Responsible Lighting®

W		2	A		
N N					
				-Ye	



Fixture Type:	
Catalog Number:	
Project:	

Location:

PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

FEATURES

- Energy Star[®] rated
- Title 24 California Energy Comission Compliant (90 CRI versions)
- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

SPECIFICATIONS

Construction: Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

J-Box (New Construction): Seven knockouts and four Romex[®] style wiring connectors provided for ease of installation. Rated for branch wiring.

Driver: 120VAC Input

Light Source: High output LED (included with housing)

Dimming: Dim to 10% with electronic low voltage (ELV) dimmer.

Mounting: Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 4½" × 4½" cutout.

Finish: Abrasion resistant powder coat paint in Black (BK).

Standards: ETL & cETL Damp Location listed

			Power	Beam	Color Temp	CRI	Lumens	CBCP	Finish
				F 25	927 2700k 930 3000k		710 785	1886 2176	BK White trim with black interior
15" H-978" 5½" ₹	85%" 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	MT-3LD1111NA New Construction Non-IC, Airtight	11W	F 25	935 3500k 940 4000k		795 805	2184 2224	WT White trim with white interior
					927 2700k 930 3000k		705 775	911 1015	BK White trim with black interior
				W 45	935 3500k 940 4000k		785 795	1024 1042	WT White trim with white interior
4 ⁵ /8"6 ¹ /8"	$\frac{1}{2} \left[\bigcup_{i=1}^{n} \frac{1}{2} 4 \frac{3}{4}^{n} \right]_{i=1}^{n} 4 \frac{3}{4}^{n} $	MT-3LD1111R Remodel Non-IC	11W	F 35	927 2700k 930 3000k		710 785	1886 2176	BK White trim with black interior
				F 25	935 3500k 940 4000k		795 805	2184 2224	WT White trim with white interior
					927 2700k 930 3000k		705 775	911 1015	BK White trim with black interior
				W 45	935 3500k 940 4000k		785 795	1024 1042	WT White trim with white interior

Example: MT-3LD111R-F30-BK

WAC Lighting www.waclighting.com Phone (800) 526.2588 • Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive • Port Washington, NY 11050 Phone (516) 515.5000 • Fax (516) 515.5050 **Western Distribution Center** 1750 Archibald Avenue • Ontario, CA 91760 Phone (800) 526.2588 • Fax (800) 526.2585

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. MAR 2017