


# MT-3LD211 - 2 Lights

## Mini LED Multiple Spots

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

Integral housing adjustable recessed spot light.

### FEATURES

- Energy Star® rated
- Title 24 California Energy Commission Compliant (90 CRI versions)
- Individually adjustable luminaires
- Complete unit includes housing & trim
- All housings are Non-IC rated
- 30° visual cutoff for glare control
- 25° vertical tilt. 350° horizontal rotation.

### SPECIFICATIONS

**Construction:** Die-cast aluminum heat sink painted black. Trim, housing and junction box are 20 gauge steel. Frame and hanger bars are heavy gauge galvanized steel.

**J-Box (New Construction):** Seven knockouts and four Romex® style wiring connectors provided for ease of installation. Rated for branch wiring.

**Driver:** 120VAC Input

**Light Source:** High output LED (included with housing)


**Dimming:** Dim to 10% with electronic low voltage (ELV) dimmer.

**Mounting:** Supplied with hanger bars, adjustable from 14½"-25" to accommodate various joist construction and grid sizes. Hanger bars include a captive mounting "screw-nail" for ease of installation. Accommodates surface up to 1" thick. 8½" x 4½" cutout.

**Finish:** Abrasion resistant powder coat paint in Black (BK).

**Standards:** ETL & cETL Damp Location listed

		Power	Beam	Color Temp	CRI	Lumens	CBCP	Finish
<p><b>MT-3LD211NA</b> New Construction Non-IC, Airtight</p> <p>22W</p>	F	25°	<b>927</b>	2700K	90	710 x2	1886 x2	<b>BK</b> White trim with black interior
			<b>930</b>	3000K	90	785 x2	2176 x2	<b>WT</b> White trim with white interior
			<b>935</b>	3500K	90	795 x2	2184 x2	
			<b>940</b>	4000K	90	805 x2	2224 x2	
<p><b>MT-3LD211R</b> Remodel Non-IC</p> <p>22W</p>	W	45°	<b>927</b>	2700K	90	705 x2	911 x2	<b>BK</b> White trim with black interior
			<b>930</b>	3000K	90	775 x2	1015 x2	<b>WT</b> White trim with white interior
			<b>935</b>	3500K	90	785 x2	1024 x2	
			<b>940</b>	4000K	90	795 x2	1042 x2	
<p><b>MT-3LD211R</b> Remodel Non-IC</p> <p>22W</p>	F	25°	<b>927</b>	2700K	90	710 x2	1886 x2	<b>BK</b> White trim with black interior
			<b>930</b>	3000K	90	785 x2	2176 x2	<b>WT</b> White trim with white interior
			<b>935</b>	3500K	90	795 x2	2184 x2	
			<b>940</b>	4000K	90	805 x2	2224 x2	
<p><b>MT-3LD211R</b> Remodel Non-IC</p> <p>22W</p>	W	45°	<b>927</b>	2700K	90	705 x2	911 x2	<b>BK</b> White trim with black interior
			<b>930</b>	3000K	90	775 x2	1015 x2	<b>WT</b> White trim with white interior
			<b>935</b>	3500K	90	785 x2	1024 x2	
			<b>940</b>	4000K	90	795 x2	1042 x2	



Example: **MT-3LD211R-F30-BK**

### WAC Lighting

www.waclighting.com

Phone (800) 526.2588 • Fax (800) 526.2585

### Headquarters/Eastern Distribution Center

44 Harbor Park Drive • Port Washington, NY 11050

Phone (516) 515.5000 • Fax (516) 515.5050

### Western Distribution Center

1750 Archibald Avenue • Ontario, CA 91760

Phone (800) 526.2588 • Fax (800) 526.2585