

TUBE ARCHITECTURAL DS-WD05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 20% (120V only)
 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WD05 5" 27W x 2</p>	S27S	2700K	85	1680 x 2	8526 x 2	62 x 2	Straight up or down 18°	
	S927S	2700K	90	1800 x 2	9151 x 2	67 x 2		
	S30S	3000K	85	1700 x 2	8639 x 2	63 x 2		
	S930S	3000K	90	1995 x 2	10126 x 2	74 x 2		
	S35S	3500K	85	2190 x 2	11118 x 2	81 x 2		
	S40S	4000K	85	2260 x 2	11483 x 2	84 x 2		
	N27S	2700K	85	1730 x 2	5513 x 2	64 x 2	Straight up or down 25°	
	N927S	2700K	90	1855 x 2	5918 x 2	69 x 2		
	N30S	3000K	85	1750 x 2	5587 x 2	65 x 2		
	N930S	3000K	90	2055 x 2	6548 x 2	76 x 2		
	N35S	3500K	85	2255 x 2	7190 x 2	84 x 2		
	N40S	4000K	85	2330 x 2	7426 x 2	86 x 2		
	F27S	2700K	85	1725 x 2	4246 x 2	64 x 2	Straight up or down 33°	
	F927S	2700K	90	1850 x 2	4557 x 2	69 x 2		
	F30S	3000K	85	1745 x 2	4302 x 2	65 x 2		
	F930S	3000K	90	2045 x 2	5043 x 2	76 x 2		
	F35S	3500K	85	2245 x 2	5537 x 2	83 x 2		
	F40S	4000K	85	2320 x 2	5719 x 2	86 x 2		
	F27A	2700K	85	1815 x 2		67 x 2	Away from the wall	
	F927A	2700K	90	1950 x 2	n/a	72 x 2		
F30A	3000K	85	1840 x 2	n/a	68 x 2			
F930A	3000K	90	2155 x 2	n/a	80 x 2			
F35A	3500K	85	2370 x 2	n/a	88 x 2			
F40A	4000K	85	2445 x 2	n/a	91 x 2			
F27B	2700K	85	1815 x 2		67 x 2	Towards the wall		
F927B	2700K	90	1950 x 2	n/a	72 x 2			
F30B	3000K	85	1840 x 2	n/a	68 x 2			
F930B	3000K	90	2155 x 2	n/a	80 x 2			
F35B	3500K	85	2370 x 2	n/a	88 x 2			
F40B	4000K	85	2445 x 2	n/a	91 x 2			
F27C	2700K	85	1815 x 2		67 x 2	One side each		
F927C	2700K	90	1950 x 2	n/a	72 x 2			
F30C	3000K	85	1840 x 2	n/a	68 x 2			
F930C	3000K	90	2155 x 2	n/a	80 x 2			
F35C	3500K	85	2370 x 2	n/a	88 x 2			
F40C	4000K	85	2445 x 2	n/a	91 x 2			

BK	Black	
WT	White	
BZ	Bronze	
GH	Graphite	

DS-WD05- _____ - _____ Example: **DS-WD05-F930A-WT**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WD06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 20% (120V only)
 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 70,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WD06 6" 35W x 2</p>	S27S	2700K	85	1875 x 2	8911	52 x 2	Straight up and down 19°	BK Black WT White BZ Bronze GH Graphite
	S927S	2700K	90	2400 x 2	11392	67 x 2		
	S30S	3000K	85	2000 x 2	9500	56 x 2		
	S930S	3000K	90	2170 x 2	10317	60 x 2		
	S35S	3500K	85	2500 x 2	11884	69 x 2		
	S40S	4000K	85	2450 x 2	11639	68 x 2		
	N27S	2700K	85	1830 x 2	4642	51 x 2	Straight up and down 30°	
	N927S	2700K	90	2340 x 2	5935	65 x 2		
	N30S	3000K	85	1950 x 2	4949	54 x 2		
	N930S	3000K	90	2120 x 2	5374	59 x 2		
	N35S	3500K	85	2440 x 2	6191	68 x 2		
	N40S	4000K	85	2390 x 2	6063	66 x 2		
	F27S	2700K	85	1840 x 2	3310	51 x 2	Straight up and down 40°	
	F927S	2700K	90	2355 x 2	4231	65 x 2		
	F30S	3000K	85	1965 x 2	3528	55 x 2		
	F930S	3000K	90	2130 x 2	3832	59 x 2		
	F35S	3500K	85	2455 x 2	4414	68 x 2		
	F40S	4000K	85	2405 x 2	4323	67 x 2		
	F27A	2700K	85	2225 x 2		62 x 2	Away from the wall	
	F927A	2700K	90	2840 x 2		79 x 2		
F30A	3000K	85	2370 x 2	n/a	66 x 2			
F930A	3000K	90	2575 x 2		72 x 2			
F35A	3500K	85	2965 x 2		82 x 2			
F40A	4000K	85	2905 x 2		81 x 2			
F27B	2700K	85	2225 x 2		62 x 2	Towards the wall		
F927B	2700K	90	2840 x 2		79 x 2			
F30B	3000K	85	2370 x 2	n/a	66 x 2			
F930B	3000K	90	2575 x 2		72 x 2			
F35B	3500K	85	2965 x 2		82 x 2			
F40B	4000K	85	2905 x 2		81 x 2			
F27C	2700K	85	2225 x 2		62 x 2	One side each		
F927C	2700K	90	2840 x 2		79 x 2			
F30C	3000K	85	2370 x 2	n/a	66 x 2			
F930C	3000K	90	2575 x 2		72 x 2			
F35C	3500K	85	2965 x 2		82 x 2			
F40C	4000K	85	2905 x 2		81 x 2			

DS-WD06- _____ - _____ Example: **DS-WD06-F930A-WT**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WD08

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 80,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WD08 8" 54W x 2</p>	S27S	2700K	85	2860 x 2	20455	53 x 2	Straight up and down 14°	BK Black WT White BZ Bronze GH Graphite
	S927S	2700K	90	3365 x 2	24065	62 x 2		
	S30S	3000K	85	3230 x 2	21796	60 x 2		
	S930S	3000K	90	3670 x 2	24490	68 x 2		
	S35S	3500K	85	4015 x 2	28660	74 x 2		
	S40S	4000K	85	3650 x 2	15121	68 x 2		
	N27S	2700K	85	2890 x 2	6851	54 x 2	Straight up and down 28°	
	N927S	2700K	90	3400 x 2	8060	63 x 2		
	N30S	3000K	85	3318 x 2	7907	61 x 2		
	N930S	3000K	90	3770 x 2	8885	70 x 2		
	N35S	3500K	85	4005 x 2	9390	74 x 2		
	N40S	4000K	85	3675 x 2	12052	68 x 2		
	F27S	2700K	85	2886 x 2	4633	53 x 2	Straight up and down 40°	
	F927S	2700K	90	3395 x 2	5450	63 x 2		
	F30S	3000K	85	3322 x 2	5407	62 x 2		
	F930S	3000K	90	3775 x 2	6075	70 x 2		
	F35S	3500K	85	4005 x 2	6490	74 x 2		
	F40S	4000K	85	3725 x 2	5443	69 x 2		
	F27A	2700K	85	2755 x 2		51 x 2	Away from the wall	
	F927A	2700K	90	3305 x 2	n/a	61 x 2		
	F30A	3000K	85	2925 x 2		54 x 2		
	F930A	3000K	90	3510 x 2		65 x 2		
	F35A	3500K	85	3685 x 2		68 x 2		
	F40A	4000K	85	3700 x 2		69 x 2		
F27B	2700K	85	2755 x 2		51 x 2	Towards the wall		
F927B	2700K	90	3305 x 2	n/a	61 x 2			
F30B	3000K	85	2925 x 2		54 x 2			
F930B	3000K	90	3510 x 2		65 x 2			
F35B	3500K	85	3685 x 2		68 x 2			
F40B	4000K	85	3700 x 2		69 x 2			
F27C	2700K	85	2755 x 2		51 x 2	One side each		
F927C	2700K	90	3305 x 2	n/a	61 x 2			
F30C	3000K	85	2925 x 2		54 x 2			
F930C	3000K	90	3510 x 2		65 x 2			
F35C	3500K	85	3685 x 2		68 x 2			
F40C	4000K	85	3700 x 2		69 x 2			

DS-WD08- _____ - _____ Example: **DS-WD08-F930A-WT**

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

TUBE ARCHITECTURAL DS-WS05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty
- Energy Star® Rated
- Title 24 Compliant*

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 20% (120V only)
0-10V: 100% - 20% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WS05 5" 27W</p>	S927S	2700K	90*	1680	8526	62	Straight up or down 18°	
	S27S	2700K	85	1800	9151	67		
	S930S	3000K	90*	1700	8639	63		
	S30S	3000K	85	1995	10126	74		
	S35S	3500K	85	2190	11118	81		
	S40S	4000K	85	2260	11483	84		
	N927S	2700K	90*	1730	5513	64	Straight up or down 25°	
	N27S	2700K	85	1855	5918	69		
	N930S	3000K	90*	1750	5587	65		
	N30S	3000K	85	2055	6548	76		
	N35S	3500K	85	2255	7190	84		
	N40S	4000K	85	2330	7426	86		
	F927S	2700K	90*	1725	4246	64	Straight up or down 33°	
	F27S	2700K	85	1850	4557	69		
	F930S	3000K	90*	1745	4302	65		
	F30S	3000K	85	2045	5043	76		
	F35S	3500K	85	2245	5537	83		
	F40S	4000K	85	2320	5719	86		
	F927A	2700K	90*	1815		67	Away from the wall	
	F27A	2700K	85	1950	n/a	72		
F930A	3000K	90*	1840	n/a	68			
F30A	3000K	85	2155	n/a	80			
F35A	3500K	85	2370	n/a	88			
F40A	4000K	85	2445	n/a	91			
F927B	2700K	90*	1815		67	Towards the wall		
F27B	2700K	85	1950	n/a	72			
F930B	3000K	90*	1840	n/a	68			
F30B	3000K	85	2155	n/a	80			
F35B	3500K	85	2370	n/a	88			
F40B	4000K	85	2445	n/a	91			

BK Black
WT White
BZ Bronze
GH Graphite

DS-WS05-_____ - _____

Example: **DS-WS05-F930A-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-WS06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty
- Energy Star® Rated

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 20% (120V only)
0-10V: 100% - 20% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DS-WS06 6" 36W</p>	S927S	2700K	90	1875	8911	52	Straight up or down 19°	BK Black WT White BZ Bronze GH Graphite
	S27S	2700K	85	2400	11392	67		
	S930S	3000K	90	2000	9500	56		
	S30S	3000K	85	2170	10317	60		
	S35S	3500K	85	2500	11884	69		
	S40S	4000K	85	2450	11639	68		
	N927S	2700K	90	1830	4642	51	Straight up or down 30°	
	N27S	2700K	85	2340	5935	65		
	N930S	3000K	90	1950	4949	54		
	N30S	3000K	85	2120	5374	59		
	N35S	3500K	85	2440	6191	68		
	N40S	4000K	85	2390	6063	66		
F927S	2700K	90	1840	3310	51	Straight up or down 40°		
F27S	2700K	85	2355	4231	65			
F930S	3000K	90	1965	3528	55			
F30S	3000K	85	2130	3832	59			
F35S	3500K	85	2455	4414	68			
F40S	4000K	85	2405	4323	67			
F927A	2700K	90	2225		62	Away from the wall		
F27A	2700K	85	2840		79			
F930A	3000K	90	2370	n/a	66			
F30A	3000K	85	2575		72			
F35A	3500K	85	2965		82			
F40A	4000K	85	2905		81			
F927B	2700K	90	2225		62	Towards the wall		
F27B	2700K	85	2840		79			
F930B	3000K	90	2370	n/a	66			
F30B	3000K	85	2575		72			
F35B	3500K	85	2965		82			
F40B	4000K	85	2905		81			

DS-WS06- _____ - _____

Example: **DS-WS06-F930A-WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

TUBE ARCHITECTURAL DS-WS08

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty
- Energy Star® Rated

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: 0-10V: 100% - 20% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 80,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, ETL & cETL wet location listed

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
	S927S	2700K	90	2860	20455	53	Straight up or down 14°		
		S27S	2700K	85	3365	24065			62
		S930S	3000K	90	3230	21796			60
		S30S	3000K	85	3670	24490			68
		S35S	3500K	85	4015	28660			74
		S40S	4000K	85	3650	15121			68
	N927S	2700K	90	2890	6851	54	Straight up or down 28°		
		N27S	2700K	85	3400	8060			63
		N930S	3000K	90	3318	7907			61
		N30S	3000K	85	3770	8885			70
		N35S	3500K	85	4005	9390			74
		N40S	4000K	85	3675	12052			68
F927S	2700K	90	2886	4633	53	Straight up or down 40°			
	F27S	2700K	85	3395	5450			63	
	F930S	3000K	90	3322	5407			62	
	F30S	3000K	85	3775	6075			70	
	F35S	3500K	85	4005	6490			74	
	F40S	4000K	85	3725	5443			69	
F927A	2700K	90	2755		51	Away from the wall			
	F27A	2700K	85	3305				61	
	F930A	3000K	90	2925	n/a			54	
	F30A	3000K	85	3510				65	
	F35A	3500K	85	3685				68	
	F40A	4000K	85	3700				69	
F927B	2700K	90	2755		51	Towards the wall			
	F27B	2700K	85	3305				61	
	F930B	3000K	90	2925	n/a			54	
	F30B	3000K	85	3510				65	
	F35B	3500K	85	3685				68	
	F40B	4000K	85	3700				69	

BK	Black	
WT	White	
BZ	Bronze	
GH	Graphite	

DS-WS08-_____ - _____

Example: DS-WS08-F930A-WT

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760