

CUBE ARCHITECTURAL DC-CD05

LED Ceiling Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5% (120V only)
 0-10V: 100% - 1% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, UL & cUL wet location listed

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish	
 DC-CD05	27W	S Spot	18°	927	2700K	90	1680	8526	62		BK Black WT White BZ Bronze GH Graphite
				827	2700K	85	1800	9151	67		
				930	3000K	90	1700	8639	63		
				830	3000K	85	1995	10126	74		
				835	3500K	85	2190	11118	81		
				840	4000K	85	2260	11483	84		
	27W	N Narrow	25°	927	2700K	90	1730	5513	64		
				827	2700K	85	1855	5918	69		
				930	3000K	90	1750	5587	65		
				830	3000K	85	2055	6548	76		
				835	3500K	85	2255	7190	84		
				840	4000K	85	2330	7426	86		
	27W	F Flood	33°	927	2700K	90	1725	4246	64		
				827	2700K	85	1850	4557	69		
				930	3000K	90	1745	4302	65		
830				3000K	85	2045	5043	73			
835				3500K	85	2245	5537	83			
840				4000K	85	2320	5719	86			

DC-CD05-_____ - _____

Example: **DC-CD05-N927-BK**

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

CUBE ARCHITECTURAL DC-CD06

LED Ceiling Mounts

WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
<p>DC-CD06</p>	36W	S Spot	19°	927 2700K 90 1875 8911 51	19°					
				827 2700K 85 2400 11392 65						
				930 3000K 90 2000 9500 54						
				830 3000K 85 2170 10317 59						
				835 3500K 85 2500 11884 68						
		840 4000K 85 2450 11639 66								
		N Narrow	30°	927 2700K 90 1830 4642 49	30°					
				827 2700K 85 2340 5935 63						
				930 3000K 90 1950 4949 53						
				830 3000K 85 2120 5374 57						
				835 3500K 85 2440 6191 66						
		840 4000K 85 2390 6063 65								
		F Flood	40°	927 2700K 90 1840 3310 50	40°					
				827 2700K 85 2355 4231 64						
				930 3000K 90 1965 3528 53						
830 3000K 85 2130 3832 58										
835 3500K 85 2455 4414 66										
840 4000K 85 2405 4323 65										

- BK** Black
- WT** White
- BZ** Bronze
- GH** Graphite

DC-CD06-_____-_____

Example: DC-CD06-N927-BK

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760