

CUBE ARCHITECTURAL DC-WS05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project: _____

Location: _____

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5% (120V only)
 0-10V: 100% - 1% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, UL & cUL wet location listed.

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
<p>DC-WS05 5" 27W</p>	927S	2700K	90	1680	8526	62	Straight up or down 18°		BK Black WT White BZ Bronze GH Graphite
	827S	2700K	85	1800	9151	67			
	930S	3000K	90	1700	8639	63			
	830S	3000K	85	1995	10126	74			
	835S	3500K	85	2190	11118	81			
	840S	4000K	85	2260	11483	84			
	927S	2700K	90	1730	5513	64	Straight up or down 25°		
	827S	2700K	85	1855	5918	69			
	930S	3000K	90	1750	5587	65			
	830S	3000K	85	2055	6548	76			
	835S	3500K	85	2255	7190	84			
	840S	4000K	85	2330	7426	86			
	927S	2700K	90	1725	4246	64	Straight up or down 33°		
	827S	2700K	85	1850	4557	69			
	930S	3000K	90	1745	4302	65			
	830S	3000K	85	2045	5043	76			
	835S	3500K	85	2245	5537	83			
	840S	4000K	85	2320	5719	86			
	927A	2700K	90	1815		67	Away from the wall		
	827A	2700K	85	1950	N/A	72			
	930A	3000K	90	1840	N/A	68			
	830A	3000K	85	2155	N/A	80			
	835A	3500K	85	2370	N/A	88			
	840A	4000K	85	2445	N/A	91			
927B	2700K	90	1815		67	Towards the wall			
827B	2700K	85	1950	N/A	72				
930B	3000K	90	1840	N/A	68				
830B	3000K	85	2155	N/A	80				
835B	3500K	85	2370	N/A	88				
840B	4000K	85	2445	N/A	91				

DC-WS05-_____ - _____

Example: **DC-WS05-F930A-WT**

wacighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

CUBE ARCHITECTURAL DC-WS06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 5% (120V only)
0-10V: 100% - 1% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, UL & cUL wet location listed.

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish	
<p>DC-WS06</p> <p>6" 36W</p>	927S	2700K	90	1875	8911	52	Straight up or down 19°	BK Black WT White BZ Bronze GH Graphite	
	827S	2700K	85	2400	11392	67			
	930S	3000K	90	2000	9500	56			
	830S	3000K	85	2170	10317	60			
	835S	3500K	85	2500	11884	69			
	840S	4000K	85	2450	11639	68			
		927S	2700K	90	1830	4642	51		Straight up or down 30°
		827S	2700K	85	2340	5935	65		
		930S	3000K	90	1950	4949	54		
		830S	3000K	85	2120	5374	59		
		835S	3500K	85	2440	6191	68		
		840S	4000K	85	2390	6063	66		
		927S	2700K	90	1840	3310	51		Straight up or down 40°
		827S	2700K	85	2355	4231	65		
		930S	3000K	90	1965	3528	55		
		830S	3000K	85	2130	3832	59		
		835S	3500K	85	2455	4414	68		
		840S	4000K	85	2405	4323	67		
		927A	2700K	90	2225		62		Away from the wall
		827A	2700K	85	2840	N/A	79		
		930A	3000K	90	2370		66		
		830A	3000K	85	2575		72		
		835A	3500K	85	2965		82		
		840A	4000K	85	2905		81		
	927B	2700K	90	2225		62	Towards the wall		
	827B	2700K	85	2840	N/A	79			
	930B	3000K	90	2370		66			
	830B	3000K	85	2575		72			
	835B	3500K	85	2965		82			
	840B	4000K	85	2905		81			

DC-WS06-_____ - _____

Example: **DC-WS06-F930A-WT**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760

CUBE ARCHITECTURAL DC-WD05

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5% (120V only)
 0-10V: 100% - 1% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 60,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, UL & cUL wet location listed.

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DC-WD05 5" 27W x2</p>	927S	2700K	85	1680 x 2	8526 x 2	62 x 2	Straight up and down 18°	BK Black WT White BZ Bronze GH Graphite
	827S	2700K	90	1800 x 2	9151 x 2	67 x 2		
	930S	3000K	85	1700 x 2	8639 x 2	63 x 2		
	830S	3000K	90	1995 x 2	10126 x 2	74 x 2		
	835S	3500K	85	2190 x 2	11118 x 2	81 x 2		
	840S	4000K	85	2260 x 2	11483 x 2	84 x 2		
	927S	2700K	85	1730 x 2	5513 x 2	64 x 2	Straight up and down 25°	
	827S	2700K	90	1855 x 2	5918 x 2	69 x 2		
	930S	3000K	85	1750 x 2	5587 x 2	65 x 2		
	830S	3000K	90	2055 x 2	6548 x 2	76 x 2		
	835S	3500K	85	2255 x 2	7190 x 2	84 x 2		
	840S	4000K	85	2330 x 2	7426 x 2	86 x 2		
	927S	2700K	85	1725 x 2	4246 x 2	64 x 2	Straight up and down 33°	
	827S	2700K	90	1850 x 2	4557 x 2	69 x 2		
	930S	3000K	85	1745 x 2	4302 x 2	65 x 2		
	830S	3000K	90	2045 x 2	5043 x 2	76 x 2		
	835S	3500K	85	2245 x 2	5537 x 2	83 x 2		
	840S	4000K	85	2320 x 2	5719 x 2	86 x 2		
	927A	2700K	85	1815 x 2		67 x 2	Away from the wall	
	827A	2700K	90	1950 x 2	N/A	72 x 2		
	930A	3000K	85	1840 x 2	N/A	68 x 2		
	830A	3000K	90	2155 x 2	N/A	80 x 2		
	835A	3500K	85	2370 x 2	N/A	88 x 2		
	840A	4000K	85	2445 x 2	N/A	91 x 2		
927B	2700K	85	1815 x 2		67 x 2	Towards the wall		
827B	2700K	90	1950 x 2	N/A	72 x 2			
930B	3000K	85	1840 x 2	N/A	68 x 2			
830B	3000K	90	2155 x 2	N/A	80 x 2			
835B	3500K	85	2370 x 2	N/A	88 x 2			
840B	4000K	85	2445 x 2	N/A	91 x 2			
827C	2700K	85	1815 x 2		67 x 2	One side each		
927C	2700K	90	1950 x 2	N/A	72 x 2			
830C	3000K	85	1840 x 2	N/A	68 x 2			
930C	3000K	90	2155 x 2	N/A	80 x 2			
835C	3500K	85	2370 x 2	N/A	88 x 2			
840C	4000K	85	2445 x 2	N/A	91 x 2			

DC-WD05- _____ - _____ Example: **DC-WD05-F930A-WT**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760

CUBE ARCHITECTURAL DC-WD06

LED Wall Mounts

WAC LIGHTING

Responsible Lighting®



PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cubical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

Fixture Type:

Catalog Number:

Project:

Location:

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input: Universal voltage 120V - 277VAC, 50/60Hz
Dimming: Electronic low voltage (ELV) : 100% - 5% (120V only)
 0-10V: 100% - 1% (120-277V)
Light Source: High output 3 Step Mac Adam Ellipse COB
 Rated life of 70,000 hours at L70
Finish: Electrostatically powder coated, white, black, bronze and graphite
Standards: IP65 rated, UL & cUL wet location listed.

ORDERING NUMBER

Diameter	Watt	Color Temp	CRI	Lumen	CBCP	Efficacy (lm/w)	Light Distribution	Finish
<p>DC-WD06 6" 35W x 2</p>	927S	2700K	85	1875 x 2	8911	52 x 2	Straight up and down 19°	
	827S	2700K	90	2400 x 2	11392	67 x 2		
	930S	3000K	85	2000 x 2	9500	56 x 2		
	830S	3000K	90	2170 x 2	10317	60 x 2		
	835S	3500K	85	2500 x 2	11884	69 x 2		
	840S	4000K	85	2450 x 2	11639	68 x 2		
	Straight up and down 30°	927S	2700K	85	1830 x 2	4642	51 x 2	
		827S	2700K	90	2340 x 2	5935	65 x 2	
		930S	3000K	85	1950 x 2	4949	54 x 2	
		830S	3000K	90	2120 x 2	5374	59 x 2	
		835S	3500K	85	2440 x 2	6191	68 x 2	
		840S	4000K	85	2390 x 2	6063	66 x 2	
	Straight up and down 40°	927S	2700K	85	1840 x 2	3310	51 x 2	
		827S	2700K	90	2355 x 2	4231	65 x 2	
		930S	3000K	85	1965 x 2	3528	55 x 2	
		830S	3000K	90	2130 x 2	3832	59 x 2	
		835S	3500K	85	2455 x 2	4414	68 x 2	
		840S	4000K	85	2405 x 2	4323	67 x 2	
	Away from the wall	927A	2700K	85	2225 x 2	N/A	62 x 2	
		827A	2700K	90	2840 x 2		79 x 2	
		930A	3000K	85	2370 x 2		66 x 2	
		830A	3000K	90	2575 x 2		72 x 2	
		835A	3500K	85	2965 x 2		82 x 2	
		840A	4000K	85	2905 x 2		81 x 2	
Towards the wall	927B	2700K	85	2225 x 2	N/A	62 x 2		
	827B	2700K	90	2840 x 2		79 x 2		
	930B	3000K	85	2370 x 2		66 x 2		
	830B	3000K	90	2575 x 2		72 x 2		
	835B	3500K	85	2965 x 2		82 x 2		
	840B	4000K	85	2905 x 2		81 x 2		
One side each	827C	2700K	85	2225 x 2	N/A	62 x 2		
	927C	2700K	90	2840 x 2		79 x 2		
	830C	3000K	85	2370 x 2		66 x 2		
	930C	3000K	90	2575 x 2		72 x 2		
	835C	3500K	85	2965 x 2		82 x 2		
	840C	4000K	85	2905 x 2		81 x 2		



DC-WD06- - Example: **DC-WD06-F930A-WT**

waclighting.com
 Phone (800) 526.2588
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center
 44 Harbor Park Drive
 Port Washington, NY 11050

Central Distribution Center
 1600 Distribution Ct
 Lithia Springs, GA 30122

Western Distribution Center
 1750 Archibald Avenue
 Ontario, CA 91760