

# TUBE ARCHITECTURAL DS-CD05

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- Title 24 Compliant\*
- Energy Star® rated
- Solid aluminum construction
- 39° visual cutoff angle for glare control
- 5 year warranty

### SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 20% (120V only)  
0-10V: 100% - 20% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 60,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed

### ORDERING NUMBER

Diameter	Watt	Beam	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish						
 <b>DS-CD05</b>	27W	18° Spot	<b>S927</b> 2700K 90* 1680 8526 62	18°	<b>S27</b> 2700K 85 1800 9151 67			<b>S930</b> 3000K 90* 1700 8639 63	<b>S30</b> 3000K 85 1995 10126 74	<b>S35</b> 3500K 85 2190 11118 81	<b>S40</b> 4000K 85 2260 11483 84				
			<b>N927</b> 2700K 90* 1730 5513 64		<b>N27</b> 2700K 85 1855 5918 69			<b>N930</b> 3000K 90* 1750 5587 65	<b>N30</b> 3000K 85 2055 6548 76	<b>N35</b> 3500K 85 2255 7190 84	<b>N40</b> 4000K 85 2330 7426 86				
			25° Narrow		<b>F927</b> 2700K 90* 1725 4246 64			25°	<b>F27</b> 2700K 85 1850 4557 69		<b>F930</b> 3000K 90* 1745 4302 65		<b>F30</b> 3000K 85 2045 5043 73	<b>F35</b> 3500K 85 2245 5537 83	<b>F40</b> 4000K 85 2320 5719 86
					<b>F927</b> 2700K 90* 1725 4246 64				<b>F27</b> 2700K 85 1850 4557 69		<b>F930</b> 3000K 90* 1745 4302 65		<b>F30</b> 3000K 85 2045 5043 73	<b>F35</b> 3500K 85 2245 5537 83	<b>F40</b> 4000K 85 2320 5719 86
					33° Flood				33°						

**DS-CD05-\_\_\_\_\_ - \_\_\_\_\_**

Example: **DS-CD05-N927-BK**

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# TUBE ARCHITECTURAL DS-CD06

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- Energy Star® rated
- Solid aluminum construction
- 38° visual cutoff angle for glare control
- 5 year warranty

### SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz
- Dimming:** Electronic low voltage (ELV) : 100% - 20% (120V only)  
0-10V: 100% - 20% (120-277V)
- Light Source:** High output 3 Step Mac Adam Ellipse COB  
Rated life of 70,000 hours at L70
- Finish:** Electrostatically powder coated, white, black, bronze and graphite
- Standards:** IP65 rated, ETL & cETL wet location listed

### ORDERING NUMBER

Diameter	Watt	Beam	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
 <b>DS-CD06</b>	36W	19° Spot	<b>S927</b> 2700K	90	1875	8911	51		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
			<b>S27</b> 2700K	85	2400	11392	65		
			<b>S930</b> 3000K	90	2000	9500	54		
			<b>S30</b> 3000K	85	2170	10317	59		
			<b>S35</b> 3500K	85	2500	11884	68		
		<b>S40</b> 4000K	85	2450	11639	66			
		30° Narrow	<b>N927</b> 2700K	90	1830	4642	49		
			<b>N27</b> 2700K	85	2340	5935	63		
			<b>N930</b> 3000K	90	1950	4949	53		
			<b>N30</b> 3000K	85	2120	5374	57		
			<b>N35</b> 3500K	85	2440	6191	66		
		<b>N40</b> 4000K	85	2390	6063	65			
		40° Flood	<b>F927</b> 2700K	90	1840	3310	50		
			<b>F27</b> 2700K	85	2355	4231	64		
			<b>F930</b> 3000K	90	1965	3528	53		
<b>F30</b> 3000K	85		2130	3832	58				
<b>F35</b> 3500K	85		2455	4414	66				
<b>F40</b> 4000K	85	2405	4323	65					

**DS-CD06-\_\_\_\_\_ - \_\_\_\_\_**

Example: **DS-CD06-N927-BK**

wacighting.com  
Phone (800) 526.2588  
Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
44 Harbor Park Drive  
Port Washington, NY 11050

Central Distribution Center  
1600 Distribution Ct  
Lithia Springs, GA 30122

Western Distribution Center  
1750 Archibald Avenue  
Ontario, CA 91760

# TUBE ARCHITECTURAL DS-CD08

## LED Ceiling Mounts

# WAC LIGHTING

Responsible Lighting®



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

### PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

### FEATURES

- Energy Star® rated
- Solid aluminum construction
- 43° visual cutoff angle for glare control
- 5 year warranty

### SPECIFICATIONS

- Input:** Universal voltage 120V - 277VAC, 50/60Hz  
**Dimming:** 0-10V: 100% - 20% (120-277V)  
**Light Source:** High output 3 Step Mac Adam Ellipse COB  
 Rated life of 80,000 hours at L70  
**Finish:** Electrostatically powder coated, white, black, bronze and graphite  
**Standards:** IP65 rated, ETL & cETL wet location listed

### ORDERING NUMBER

Diameter	Watt	Beam	Color Temp	CRI	Lumens	CBCP	Efficacy (Lm/W)	Light Distribution	Finish
 <b>DS-CD08</b>	54W	14° Spot	<b>S927</b> 2700K	90	2860	20455	53		<b>BK</b> Black <b>WT</b> White <b>BZ</b> Bronze <b>GH</b> Graphite
			<b>S27</b> 2700K	85	3365	24065	62		
			<b>S930</b> 3000K	90	3230	21796	60		
			<b>S30</b> 3000K	85	3670	24490	68		
			<b>S35</b> 3500K	85	4015	28660	74		
			<b>S40</b> 4000K	85	3650	15121	68		
		28° Narrow	<b>N927</b> 2700K	90	2890	6851	54		
			<b>N27</b> 2700K	85	3400	8060	63		
			<b>N930</b> 3000K	90	3318	7907	61		
			<b>N30</b> 3000K	85	3770	8885	70		
			<b>N35</b> 3500K	85	4005	9390	74		
			<b>N40</b> 4000K	85	3675	12052	68		
		40° Flood	<b>F927</b> 2700K	90	2886	4633	53		
			<b>F27</b> 2700K	85	3395	5450	63		
			<b>F930</b> 3000K	90	3322	5407	62		
			<b>F30</b> 3000K	85	3775	6075	70		
			<b>F35</b> 3500K	85	4005	6490	74		
			<b>F40</b> 4000K	85	3725	5443	69		

**DS-CD08-\_\_\_\_\_ - \_\_\_\_\_**

Example: **DS-CD08-N927-BK**

wacighting.com  
 Phone (800) 526.2588  
 Fax (800) 526.2585

Headquarters/Eastern Distribution Center  
 44 Harbor Park Drive  
 Port Washington, NY 11050

Central Distribution Center  
 1600 Distribution Ct  
 Lithia Springs, GA 30122

Western Distribution Center  
 1750 Archibald Avenue  
 Ontario, CA 91760