DECK & PATIO - CIRCLE





LANDSCAPE LIGHTING




Fixture Type:

Project:

Location:

Catalog Number:



PRODUCT DESCRIPTION

Deck and patio light with superb forward-throw light distribution

FEATURES

- IP66 rated, Protected against powerful water jets
- Translucent lens provides for uniform diffused light output
- · Solid diecast brass or corrosion resistant aluminum alloy
- ADA compliant
- Maintains constant lumen output against voltage drop
- UL 1838 Listed

SPECIFICATIONS

Input: 9-15VAC (Transformer is required)

 Power:
 2.8W / 4.6VA

 Brightness:
 60 lm

 CRI:
 90+

 Rated Life:
 50,000 hours

ORDERING NUMBER

		Color Temp	Finish	
3011	Circle	27 2700K 30 3000K	BBR Bronze on Brass BK Black on Aluminum BZ Bronze on Aluminum WT White on Aluminum)

3011-

Example: **3011-30BZ**

DECK & PATIO - CIRCLE

3011



Magnetic Transformers

Stainless Steel, 12-15V output, IP65 rated, UL 1838 listed See transformer spec sheet for details and its accessories

9075-TRN-SS *75W Max*

9150-TRN-SS *150W Max*

9300-TRN-SS 300W Max **9600-TRN-SS** 600W Max



TESTED MAGNETIC LOW VOLTAGE(MLV) DIMMERS

Luminaire	Dimmer						
	Manufacturer	Family	Model	Power Rating	Range*	Note	
	Lutron	Diva	DVLV-600	600W	33% - 100%	Output maxes at 50% dimming level	
3011		Skylark	SLV-600P	600W	28% - 100%	Output maxes at 50% dimming level	
		Skylark	S-10P	1000W		Not recommended	

^{*}Low end of this range is determined by output current which may not directly translate to the perceived light output

WAC Lighting fixtures are compatible with a variety of dimmers. For your convenience we have included a compatibility chart showing dimmers which have been tested with our products. The recommended list below is based upon testing conducted in a lab, and the results can vary in certain field applications due to a number of factors. Exclusion from the list does not imply incompatibility, just that it has not been tested by WAC Lighting. Please reference the dimmer manufacturer's instructions for installation, or contact a WAC lighting professional at 800-526-2588.