

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Disc

Ceiling and Wall Mount

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-304 4"	930 3000K - 90	12W	725	BN Brushed Nickel
FM-306 6"	940 4000K - 90	15W	945	BZ Bronze
FM-306-JB 6"			950	WT White

Example: **FM-304-930-BN**

DESCRIPTION

Multiple high-powered LEDs illuminate an acrylic diffuser uniformly without socket shadows, which are common in conventional flush mounts. This multi-purpose Wet Location, Energy Star Rated flush mount can be mounted without a transformer on a ceiling or on a wall in a junction box, and also includes an optional retrofit kit with an A19 socket designed to fit into an existing 3" - 6" recessed unit. The disc is available in 6" and 4" sizes, and various finishes and color temperature options.

FEATURES

- Multiple LED array for uniform illumination
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Construction:	Die-cast aluminum with white acrylic diffuser
Power:	15W, 12W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50000 Hours
Mounting:	Retrofit over a 5" or 6" recessed can or install over a 3" or 4" junction box, Can be mounted on ceiling or wall in all orientations, Install over a 3" or 4" junction box, Retrofit over a 4" recessed can or install over a 3" or 4" junction box
Finish:	Electrostatically Powder Coated White, Bronze, Electroplated Brushed Nickel
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2016 Compliant, ADA

REPLACEMENT PARTS

FM-306-RFK - 6" Retrofit Kit
 FM-304-RFK - 4" Retrofit Kit



FINISHES



LINE DRAWING

