WAC LIGHTING

BLAZE 6" Square

Remodel Downlight

Fixture Type:

Catalog Number:

Project:

Location:

	0				
Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R6DSDR	F 55°	9CS 2700K/3000K/3500K /4000K/5000K - 90	2060	2340	WT White

Example: R6DSDR-F9CS-WT

DESCRIPTION

Minimum profile downlight with metal conduit and driver included for easy remodel or new construction installation.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as remodel, but new construction frame available
- Metal Conduit with Quick Connect to allow for easy installation
- Driver included
- 5 year warranty


SPECIFICATIONS

Construction:	Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver		
	Box		
Power:	25W		
Input:	120-277 VAC, 50/60Hz		
Dimming:	nming: ELV: 100-10% , TRIAC: 100-5%		
Light Source:	Integrated LED		
Lens:	Frosted TIR lens		
Rated Life:	ted Life: 50000 Hours		
Mounting:	Heavy gauge rentention clips secures fixture to ceiling	LINE	
Cut Out:	5 1/2"		
Finish:	eiling Thickness: 1/2" - 1 1/2"		
Ceiling Thickness:			
Operating Temp:			
Standards:	ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant, IC, Airtight	31/2"	



ISHES:

DRAWING:



WAC LIGHTING

BLAZE 6" Square

Remodel Downlight

ACCESSORIES

Model

Description

Fixture Type:

Catalog Number:

Project:

Location:

Finish