


# ODYSSEY

F-005L

52" Ceiling Fan

WAC  
SMART FANS



## PRODUCT DESCRIPTION

Make a statement with Odyssey, an updated twist on a classic style. The bold, round shape of the body and smooth asymmetrical blades are accompanied by the familiar beaded fan speed and light chains, creating a model that is equal parts refreshing and recognizable. Make it smart by downloading the app for additional functionality.

## FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Luminaire cover not available
- Includes remote control with wall cradle
- Wall control for 3, 4-way control sold separately
- Compatible with WAC app

## AIRFLOW/ENERGY EFFICIENCY

Weighted-Average/High Airflow CFM:	3221/5042
Weighted-Average/High Energy Use (W):	21/28
Estimated Yearly Energy Cost (\$):	6
Efficiency (CFM/W):	155
Max RPM:	165

## ORDER NUMBER

Model	Housing	Blade
F-005L	BN Brushed Nickel	BN Brushed Nickel
	MB Matte Black	MB Matte Black
	MW Matte White	MW Matte White

## F-005L-

Example: F-005L-MB

\*This fan comes uni-pack - blade select options are not available



The WAC app synchronizes seamlessly with smart home devices you already own



waclighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters/Eastern Distribution Center

44 Harbor Park Drive

Port Washington, NY 11050

Central Distribution Center

1600 Distribution Ct

Lithia Springs, GA 30122

Western Distribution Center

1750 Archibald Avenue

Ontario, CA 91760

# ODYSSEY

F-005L

52" Ceiling Fan

**WAC**  
**SMART FANS**

## OPTIONAL ACCESSORIES

Bluetooth Wall Control		WC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Additional Wall Controls can be purchased separately for multiple location control.
Bluetooth Remote Control		RC20-	WT White	Control fan speed and light brightness, and switch between Summer and Winter Modes. Compatible with WAC Smart Fans. Includes easy-to-install wall cradle and batteries.
Downrod		DR12- DR18- DR24- DR36- DR48- DR60- DR72-	12IN 18IN 24IN 36IN 48IN 60IN 72IN	All our downrods are .75 (in) and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field.
Downrod Couplers		DC-	BA MB MW	Brushed Aluminum Matte Black Matte White
Sloped Ceiling Kit		SC-		Connects two downrods together.
				Designed to accommodate buildings with steeper sloped ceilings up to 45o or 12/12 pitch.

Examples: Wall Control - **WC20-WT**, Remote Control - **RC20-WT**, Downrod - **DR12-BN**, Downrod Coupler - **DC-MB**, Sloped Ceiling Kit - **SC-MW**

## SUGGESTED DOWNRod HEIGHT USAGE

Ceiling Height	15'	14'	13'	12'	11'	10'	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

## SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13o	14-17o	18-21o	22-25o	26-29o	30-32o	33-35o	36-38o	39-41o	42-44o	45o
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

**NOTE:** Recommended maximum downrod length of 72" with 80" lead wire