

LOTOS 4" & 6" Downlight LED

Recessed R4ERDR / R6ERDR

WAC LIGHTING

Responsible Lighting®

Fixture Type:

Catalog Number:

Project: _____

Location: _____



PRODUCT DESCRIPTION

Shallow profile LED that is designed to fit in furred down ceilings without sacrificing lumen output. Available in 4" or 6" recessed and 4" or 6" adjustable LED recessed.

FEATURES

- Heavy gauge retention clips secures fixture to ceiling
- 360° Retractable Pivot: Downlight and Adjustable
- Installs into ceilings between ½" and 1½" thick
- Height: Fixture - 1¼", Driver 1¼"
- 50,000 hour rated life
- 5 year warranty
- 90 CRI
- 5-CCT Selectable Switch

ORDERING NUMBER

SPECIFICATIONS

Construction: Steel with frosted TIR lens


Input: 120 -277V

Dimming: 100% - 10% ELV, 100% - 5% TRIAC


Harmonic Distortion (THD): <20%

Operating Temperature: -20°C (-4°F) to 40°C (104°F)

Standards: Title 24 JA8-2016 Compliant; Energy Star® Rated; Wet Location listed; ETL & cETL listed



R4ERDR



Model	Power	Beam	Max Lumens	Color Temp	Finish
R4ERDR 4" Round IC - Rated, Airtight Wet Location listed	9W	W 45°	725	9CS 5-CCT Selectable 2700K-3000K-3500K- 4000K-5000K	WT White
R6ERDR 6" Round IC - Rated, Airtight Wet Location listed	15W	W 45°	1340	9CS 5-CCT Selectable 2700K-3000K-3500K- 4000K-5000K	WT White

R6ERDR-W9CS-WT

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760