

Bandeau

Outdoor Wall Sconce

Fixtu	re Type:	
Catal	og Number:	
Proje	ct:	
Locat	ion:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W21110 10"	3000K 90 3500K 90 4000K 90	BK Black	8W 8W 8W	600 600 600	180 192 180

Example: WS-W21110-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Just the right bandwidth to stream illumination

FEATURES

- Silk screen mitered tempered glass diffuser
- 3CCT (3000K/3500K/4000K) selectable switch
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 4000K,3500K,3000K

 Input:
 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum body, glass diffuser



FINISHES:




Black

REPLACEMENT PARTS

RPL-GLA-21110-OUT - Outer Glass RPL-GLA-21110-IN - Inner Glass

LINE DRAWING:



WAC LIGHTING

Bandeau

Outdoor Wall Sconce

Catalog Number:
Project:
Location:

Fixture Type:

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W21116 16"	3000K 90 3500K 90 4000K 90	BK Black	17W 17W 17W	1200 1200 1200	465 494 464

Example: WS-W21116-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Just the right bandwidth to stream illumination

FEATURES

- Silk screen mitered tempered glass diffuser
- 3CCT (3000K/3500K/4000K) selectable switch
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 4000K,3500K,3000K

 Input:
 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum body, glass diffuser



FINISHES:




Black

REPLACEMENT PARTS

RPL-GLA-21116-OUT - Outer Glass RPL-GLA-21116-IN - Inner Glass

LINE DRAWING:





Bandeau

Outdoor Wall Sconce

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-W21122 22"	3000K 90 3500K 90 4000K 90	BK Black	20W 20W 20W	1600 1600 1600	697 734 702

Example: WS-W21122-40-BK

For custom requests please contact customs@waclighting.com

DESCRIPTION

Just the right bandwidth to stream illumination

FEATURES

- Silk screen mitered tempered glass diffuser
- 3CCT (3000K/3500K/4000K) selectable switch
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

 Color Temp:
 4000K,3500K,3000K

 Input:
 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% ,TRIAC: 100-10%

Rated Life: 50000 Hours

Mounting: Can be mounted on wall in all orientations
Standards: ETL, cETL,IP65,Title 24 JA8-2019 Compliant

Wet Location Listed

Construction: Aluminum body, glass diffuser



FINISHES:



Black

REPLACEMENT PARTS

RPL-GLA-21122-OUT - Outer Glass RPL-GLA-21122-IN - Inner Glass

LINE DRAWING:

