



BASICS

LED Tape

WAC LIMITED



Fixture Type:

Catalog Number:

Project: _____

Location: _____

PRODUCT DESCRIPTION

Flexible, customizable, with a low profile. Basics LED Tape delivers precision and performance with five selectable white color temperatures from warm 2700K to cool 5000 Kelvin. Smooth robust illumination deployed from evenly placed UV coated LEDs for cove, accent and task lighting applications. Strong 3M adhesive bond for easy installation. Seamless and scalable to 40 foot lengths. Cuttable in the field. Closet rated.

FEATURES

- Damp location listed
- Title 24 Compliant
- UL/cUL listed
- Available in convenient spools up to 100ft
- Up to 40ft max distance between power supply and beginning of tape run
- Cut and securely reconnect with ease
- May be cut every 4 inches
- Good color rendering
- Suitable for installation in a clothes closet
- 50,000 hour rated life
- 5 year WAC Lighting product warranty
- 30ft max run of T24-BS1, 20 ft max run of T24-BS2 at 40ft max distance between power supply and beginning of tape run

SPECIFICATIONS

Construction:	Flexible strip light
Cutting Interval:	4"
Input:	24VDC
Lumens:	Up to 200 lm/ft
Max Run:	Refer to ordering table
CRI:	90
McAdams Steps:	3
Color Temp:	2700K / 3000K / 3500K / 4000K / 5000K
Rated Life:	50,000 hours
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	UL & cUL listed, Damp Location listed, Title 24 Compliant

ORDER NUMBER - TAPE SELECTION

System	Max Run	Power	Length	Color Temp	Color	
T24-BS1	100+lm/ft	40ft (@6ft lead wire between power supply and beginning of tape run)	1.2W/ft	15	15 ft spool (includes 2pcs T24-BS-MM-CL)	WT
				40	40 ft spool (includes 8pcs T24-BS-MM-CL)	
				100	100 ft spool (includes 20pcs T24-BS-MM-CL)	
T24-BS2	200+lm/ft	40ft (@6ft lead wire between power supply and beginning of tape run)	2.4W/ft	27	2700K	
				30	3000K	
				35	3500K	
				40	4000K	
				50	5000K	

T24-BS1-__ - __WT

Example: **T24-BS1-15-27WT**

wacighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters/Eastern Distribution Center
44 Harbor Park Drive
Port Washington, NY 11050

Central Distribution Center
1600 Distribution Ct
Lithia Springs, GA 30122

Western Distribution Center
1750 Archibald Avenue
Ontario, CA 91760









BASICS

Power Supplies and Accessories

Class 2 Power Supply (Required)

	Model	Input	Output	Dimming	
	EN-BT60-24	120VAC	24VDC 60W	ELV 100% - 10%	6 1/2" x 2 1/16" x 1 1/4" 6 ft. Output lead wires
	EN-BT96-24	120VAC	24VDC 96W	ELV 100% - 10%	
	PS-24DC-U60R-SP	120V-277VAC	24VDC 60W	ELV/ TRIAC / 0-10V	7 11/16" x 3 7/8" x 1 3/8" Universal Input, ≥ 0.9 pf Overload and short circuit protection 6" Output lead wires Longer lead wire sold separately - 24VDC Basics Extension Cable
	PS-24DC-U96R-SP	120V-277VAC	24VDC 96W	ELV/ TRIAC / 0-10V	
	PS-24DC-U288R-SP	120V-277VAC	24VDC 288W (3 x 96W)	ELV/ TRIAC / 0-10V	10 3/4" x 8 5/8" x 1 3/8" Universal Input, ≥ 0.9 pf Overload and short circuit protection 6" Output lead wires Longer lead wire sold separately - 24VDC Basics Extension Cable

Accessories

Tape to Tape Connector		T24-BS-MM-CL	10 pcs	Clear	Connects tape sections
Tape to Tape Corner Connector		T24-BS-L-CL	2 pcs	Clear	Connects tape sections
Power to Tape Connector		T24-BS-PM-CL	10 pcs	Clear	Connects power feed to tape section
Flex Y Connector		T24-BS-Y-WT T24-BS-Y-BK	1 pc	White Black	Connects tape sections and power feed, Includes LED-T-B
Flex X Connector		T24-BS-X-WT T24-BS-X-BK	1 pc	White Black	Connects tape sections and power feed, Includes LED-T-B
Low Voltage Wiring Box		LED-T-B		White	Neatly house connections for up to 2 wires
Joiner Cable		T24-BS-IC-002 T24-BS-IC-006 T24-BS-IC-012 T24-BS-IC-036 T24-BS-IC-072	2 inches 6 inches 1 foot 3 feet 6 feet	-WT White -BK Black	Extends distance between tape sections
Extension Cable		T24-BS-EX2-072 T24-BS-EX2-144 T24-BS-EX2-240 T24-BS-EX2-480	6 feet 12 feet 20 feet 40 feet	-WT White -BK Black	Extends distance between tape sections and power supply (Includes a LED-T-B & screw driver)