WAC LIGHTING

Fixture Type:

Project:

Location:

Catalog Number:

Bullet

10W H/J/L Track Luminaire

| System Type & Voltage | Model | Color Temp & CRI | Lumens | CBCP | Finish |
|-------------------------------------|-------|----------------------|--------|------|---|
| H 120 VAC J 120 VAC L 120 VAC | 7010 | 30 3000K - 90 | 850 | 1078 | BK Black BN Brushed Nickel WT White |

Example: H-7010-30-BK

DESCRIPTION

The Bullet 7010 track luminaire offers superior light output in a small, unobtrusive design. Developed for residential spaces and lower-mounted commercial applications.

FEATURES

- 350° horizontal and 90° vertical aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

| Construction: | Die-cast aluminum with frosted TIR lens | | |
|-----------------|---|--|--|
| Power: | 10W | | |
| Input: | 120 VAC, 50/60Hz | | |
| Dimming: | ELV: 100-5% , TRIAC: 100-5% | | |
| Light Source: | Integrated LED | | |
| | 3 Step Mac Adam Ellipse | | |
| Lens: | Frosted TIR Lens | | |
| Rated Life: | 50000 Hours | | |
| Finish: | Electrostatically Powder Coated:Black, Electrostatically Powder Coated::Brushed Nickel, Electrostatically Powder Coated:::White | | |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) | | |
| Standards: | ETL, cETL, Dry Location Listed, Energy Star 2.0, Title 24 JA8-2019 Compliant | | |



FINISHES:

| Black | Brushed Nickel | White |
|-------|-------------------|-------|

LINE DRAWING:

