

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Revels

Outdoor Wall Sconce

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W13324 24"	3000K	BK Black	13W	300	193
	3500K		13W	300	193
	4000K		13W	300	193

Example: **WS-W13324-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL,IP65 Wet Location Listed
Construction:	Extruded aluminum body with PC diffuser




FINISHES:



Black

LINE DRAWING:



WS-W13324

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Revels

Outdoor Wall Sconce

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W13336 36"	3000K	BK Black	17W	400	256
	3500K		17W	400	256
	4000K		17W	400	256

Example: **WS-W13336-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL,IP65 Wet Location Listed
Construction:	Extruded aluminum body with PC diffuser




FINISHES:



Black

LINE DRAWING:



WS-W13336

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Revels

Outdoor Wall Sconce

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W13348 48"	3000K	BK Black	24W	555	358
	3500K		24W	555	358
	4000K		24W	555	358

Example: **WS-W13348-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL,IP65 Wet Location Listed
Construction:	Extruded aluminum body with PC diffuser




FINISHES:



Black

LINE DRAWING:



WS-W13348

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Revels

Outdoor Wall Sconce

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W13360 60"	3000K	BK Black	28W	665	428
	3500K		28W	665	428
	4000K		28W	665	428

Example: **WS-W13360-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL,IP65 Wet Location Listed
Construction:	Extruded aluminum body with PC diffuser




FINISHES:



Black

LINE DRAWING:



WS-W13360

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Revels

Outdoor Wall Sconce

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-W13372 72"	3000K	BK Black	28W	850	547
	3500K		28W	850	547
	4000K		28W	850	547

Example: **WS-W13372-40-BK**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Balanced with geometric precision. A slim bar of light glowing between the lines of a minimal profile.

FEATURES

- Illumination on both sides with acrylic diffuser
- Built in color temperature adjustability. Switch from 3000K/3500K/4000K
- 3CCT switch installs in the junction box
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	3000K,3500K,4000K
Input:	120 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-10%
Rated Life:	54000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL,IP65 Wet Location Listed
Construction:	Extruded aluminum body with PC diffuser




FINISHES:



Black

LINE DRAWING:



WS-W13372