

# WAC LIGHTING

## Lotos - Fire Rated

Downlight 5CCT

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R4ERDR	W 180	9CS 2700K/3000K/3500K/4000K/5000K - 90	725	No	FWT White (Fire Rated)

Example: **R4ERDR-W9CS-FWT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

### DESCRIPTION

Fire rated to reduce the spread of flames and maintain the integrity of the ceiling.

### FEATURES

- Fire Rated - ASTM E119 and UL 263 tested and certified for 2 hours
- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Minimum Plenum Space Required: 4 1/2"
- Driver included
- 5 year warranty

### SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	120-277 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-5% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Standards:	ETL, cETL,Title 24 JA8 Compliant,Energy Star 2.0 Wet Location Listed
Construction:	Steel with translucent acrylic diffuser



### FINISHES:

White  
(Fire Rated)

### LINE DRAWING:

# WAC LIGHTING

## Lotos - Fire Rated

Downlight 5CCT

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R6ERDR	W 180	9CS 2700K/3000K/3500K/4000K/5000K - 90	1200	No	FWT White (Fire Rated)

Example: **R6ERDR-W9CS-FWT**

For custom requests please contact [customs@wacighting.com](mailto:customs@wacighting.com)

### DESCRIPTION

Fire rated to reduce the spread of flames and maintain the integrity of the ceiling.

### FEATURES

- Fire Rated - ASTM E119 and UL 263 tested and certified for 2 hours
- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- Minimum Plenum Space Required: 4 1/2"
- Driver included
- 5 year warranty

### SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K/5000K
Input:	120-277 VAC,50/60Hz
CRI:	90
Dimming:	ELV: 100-5% ,TRIAC: 100-5%
Rated Life:	50000 Hours
Mounting:	Heavy gauge retention clips secures fixture to ceiling
Standards:	ETL, cETL,Title 24 JA8 Compliant,Energy Star 2.0 Wet Location Listed
Construction:	Steel with translucent acrylic diffuser



### FINISHES:

White  
(Fire Rated)

### LINE DRAWING: