

91

Bullet 7010 – 5CCT			Project: Location:				
System Type & Voltage	Model	Color Temp & CRI		Lumens	CBCP	Finish	

2700K/3000K/3500K/4000K/5

CS

000K - 90

Fixture Type:

Catalog Number:

890

1017

Example: H-7010-CS-BK

DESCRIPTION

H 120 VAC

120 VAC

L 120 VAC

Bullet 7010 track luminaire offers superior light output in a small, unobtrusive design. Developed for residential spaces and lower-mounted commercial applications.

7010

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- 350° horizontal and 90° vertical aiming
- Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Construction Die-cast aluminum with frosted TIR lens

Power:

Input:

120 VAC,50/60Hz

Dimming:

ELV: 100-10%, TRIAC: 100-10%

Light Source:

Integrated LED, 3 Step Mac Adam Ellipse

Frosted TIR Lens Lens: Rated Life: 50,000 Hours

Finish: Electrostatically Powder Coated: White, Black

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Dry Location Listed, Title 24 JA8 Compliant




BK Black

WT White

FINISHES:



LINE DRAWING:



1