

WAC LIGHTING

Kenric 3.5" 5CCT

Square Trim Adjustable Downlight

| Model | Beam | Color Temp & CRI | Lumens | CBCP | Finish |
|--------|------|--|--------|------|----------|
| R3JSAT | W 36 | CS 2700K/3000K/3500K/4000K/5000K - 90 | 1420 | 3425 | WT White |

Example: **R3JSAT-WCS-WT**

DESCRIPTION

The Kenric LED recessed luminaire offers an All-In-One 5-CCT adjustable white color temperature range from warm 2700K to cool 5000K. Easy to install with rotatable multi-axis 360-degree horizontal and 30-degree vertical aimability, this low-profile fixture is constructed with die-cast aluminum and a white powder coat trim. Choose between round and square trim and trimless styles with deeply regressed LED for superior glare control. A single fixture provides both downlight and adjustable functions that deploy up to 1450 lumens with a 90 CRI for true-to-life color rendering.



FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as remodel, but new construction frame available
- Driver included
- 5 year warranty

SPECIFICATIONS


| | |
|--------------------|---|
| Construction | Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box |
| Power: | 14.5W |
| Input: | 120-277 VAC, 50/60Hz |
| Dimming: | ELV: 100-5% , 0-10V: 100-5% , TRIAC: 100-5% |
| Light Source: | Integrated LED |
| Lens: | TIR Lens |
| Rated Life: | 50,000 Hours |
| Mounting: | Heavy gauge retention clips secures fixture to ceiling |
| Cut Out: | 4.5" |
| Finish: | Electrostatically Powder Coated: White |
| Ceiling Thickness: | 1/2" - 1 1/2" |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C) |
| Standards: | ETL, cETL, Wet Location Listed, Energy Star 2.0, Title 24 JA8 Compliant, Airtight, IC |

FINISHES:



White

LINE DRAWING



WAC LIGHTING

Kenric 3.5" 5CCT

Square Trim Adjustable Downlight

Fixture Type:

Catalog Number:

Project:

Location:

ACCESSORIES

| <i>Model</i> | <i>Description</i> | <i>Finish</i> |
|---|--------------------|------------------|
|  | R3JB-FRAME | Kenric 3.5" 5CCT |