OCULARC – model: 7011-CS

H/L/J Track Luminaire

WAC

Fixture Type:

Catalog Number:

Project:

Location:



PRODUCT DESCRIPTION

Ideal for residential spaces and lower-mounted commercial installations, the OCULARC 7011-CS combines a high efficacy 5-CCT selectable COB LED with easy-to-use films for three separate beam spreads, along with an adjustable base to accommodate a variety of user preferences. With the driver and thermal/optical management encased in the die-cast housing, this compact luminaire offers a clean, efficient, versatile design that works with almost any décor. Available in H, J/J2, and L track configurations.

FEATURES

- **3 beam angle options included:**
  60° beam film pre-installed, interchangeable 30° film supplied, remove film for 17° spot beam
- Discrete, toolless integrated 5CCT switch: 2700K, 3000K, 3500K, 4000K, 5000K
- Integral driver and high output COB LED
- Outperforms halogen 65W MR16
- 350° horizontal and 90° vertical aiming
- 5 year warranty

REPLACEMENT OPTICS

17°	*Spot TIR Lens*	**TIR-HER2-OD50-S-W**
30°	*Narrow Flood Film*	**FILM-16-N**
60°	*Flood Film*	**FILM-16-F**

SPECIFICATIONS

Construction:	Die-cast aluminum with baffled front cover for glare control
Input Power:	11W at 120VAC, 50/60Hz
Power Factor:	0.98
THD(A):	< 15% Total Harmonic Distortion (Current)
Light Source:	High output 3 Step Mac Adam, Ellipse COB, 90+ CRI Rated Life of 50,000 hours at L70
Dimming:	Electronic Low Voltage (ELV) or TRIAC: 100 - 10% Reference dimming report for compatibility.
Standards:	ETL & cETL Dry Location Listed, Title 24 JA8 Compliant
Finish:	Electrostatically powder coated Black, Dark Bronze, and White. Electroplated Brushed Nickel
Operating Temperature:	-4℉ to 104℉ (-20℃ to 40℃)

EXTENSION OPTIONS

Sold Separately. Ceiling Mount and H-Track compatible only

H	*H Track*	**18**	*18"*	**BK**	*Black*
		24	*24"*	**BN**	*Brushed Nickel*
		36	*36"*	**DB**	*Dark Bronze*
		48	*48"*	**WT**	*White*

System	Model	Beam	Max Lumens	Max CBCP	Color Temp	CRI	T24	Finish
H *H Track* **L** *L Track* **J** *J/J2 Track*	**7011**	*17°* *30°* *60°*	*1025* *955* *920*	*3935* *1520* *670*	**CS** *2700K/3000K/3500K/4000K/5000K*	*90*	*Yes*	**BK** *Black* **BN** *Brushed Nickel* **DB** *Dark Bronze** **WT** *White*

* Only available in H Track

__-7011-CS-_____

Example: **H-7011-CS-BN**

waclighting.com
Phone (800) 526.2588
Fax (800) 526.2585

Headquarters, East Manufacturing Facility
44 Harbor Park Drive
Port Washington, NY 11050

South East Manufacturing Facility
1600 Distribution Ct
Lithia Springs, GA 30122

Central Manufacturing Facility
1700 South J Elmer Freeway, Ste 100
Cedar Hill, TX 75104

West Manufacturing Facility
1750 S Archibald Ave
Ontario, CA 91761

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. JAN 2025