

Charge 8010/3 - 5CCT

3 Light Track Kit

System Type & Voltage	Model	Color Temp & CRI	Lumens	CBCP	Finish
H 120 VAC	8010/3	CS 2700K/3000K/3500K/4000K/5 000K - 90	865 x 3	1006 x 3	BK Black BN Brushed Nickel DB Dark Bronze WT White

Fixture Type:

Project:

Location:

Catalog Number:

Example: H-8010/3-CS-BK

DESCRIPTION

Charge 8010 track luminaire offers superior light output in a small, unobtrusive design. Developed for residential spaces and lower-mounted commercial applications.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- 350° horizontal and 90° vertical aiming
- · Driver concealed within the fixture
- 5 year warranty

SPECIFICATIONS

Die-cast aluminum with frosted TIR lens Construction

Power: 9W x 3

Input: 120 VAC,50/60Hz

Dimming: ELV: 100-10%, TRIAC: 100-10%

Light Source: Integrated LED, 3 Step Mac Adam Ellipse

Lens: Frosted TIR Lens **Rated Life:** 50.000 Hours

Finish: Electrostatically Powder Coated: Black, Electroplated Brushed


Nickel, Dark Bronze, White

Operating Temp: -4°F to 104°F (-20°C to 40°C)

Standards: ETL, cETL, Dry Location Listed, Title 24 JA8 Compliant



FINISHES:



Brushed Nickel Bronze

White