

Straitaway

Bath & Wall 4CCT

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Λ	Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
	WS-51524 24"	2700K	BK Black BN Brushed Nickel	18.5W	1665	916
		3000K				
		3500K				
		4000K				

Example: WS-51524-40-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Clean and Simple. A rounded linear silhouette features and white diffuser adorned with triangular end caps and square backplate designed to provide abundant and balanced light through an understated aesthetic.

FEATURES

- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Decorative conversion plate to accommodate standard 4" junction box is included
- · Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp: 2700K,3000K,3500K,4000K

120/277V,50/60Hz Input:

CRI 90

ELV: 100-10%, TRIAC: 100-10% Dimming:

Rated Life: 50.000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed


Construction Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:





Straitaway

Bath & Wall 4CCT

Fixture Type:
Catalog Number:
Project:
Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-51532 32"	2700K	BK Black BN Brushed Nickel	24.5W	2205	1213
	3000K				
	3500K				
	4000K				

Example: WS-51532-40-BN

For custom requests please contact customs@waclighting.com

DESCRIPTION

Clean and Simple. A rounded linear silhouette features and white diffuser adorned with triangular end caps and square backplate designed to provide abundant and balanced light through an understated aesthetic.

FEATURES

- Built in color temperature adjustability. Switch from
- 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Decorative conversion plate to accommodate standard 4" junction box is included
- · Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp: 2700K,3000K,3500K,4000K

120/277V,50/60Hz Input:

CRI 90

ELV: 100-10%, TRIAC: 100-10% Dimming:

Rated Life: 50,000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed

Construction Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:

