

WAC LIGHTING

Boulevard

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-62518 18"	2700K	AB Aged Brass BN Brushed Nickel	15W	1200	989
	3000K				
	3500K				
	4000K				

Example: **WS-62518-40-BN**

For custom requests please contact customs@wacighting.com

DESCRIPTION

End to End. A triangular clear diffuser encases a rod of LEDs, emitting a generous and even expression of illumination.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Decorative conversion plate to accommodate standard 4" junction box is included
- Driver included
- 5 Year warranty

SPECIFICATIONS

Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with acrylic diffuser




FINISHES:



Aged Brass

Brushed Nickel

LINE DRAWING:



WS-62518

WAC LIGHTING

Boulevard

Wall Sconce 4CCT

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
WS-62524 24"	2700K	AB Aged Brass BN Brushed Nickel	20W	1800	1422
	3000K				
	3500K				
	4000K				

Example: **WS-62524-40-BN**

For custom requests please contact customs@wacighting.com

DESCRIPTION

End to End. A triangular clear diffuser encases a rod of LEDs, emitting a generous and even expression of illumination.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option to pre-select color temperature or adjust in the field
- Decorative conversion plate to accommodate standard 4" junction box is included
- Driver included
- 5 Year warranty

SPECIFICATIONS


Color Temp:	2700K,3000K,3500K,4000K
Input:	120-277V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	54,000 Hours
Mounting:	Can be mounted on wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Damp Location Listed
Construction	Aluminum hardware with acrylic diffuser



FINISHES:



LINE DRAWING:



WS-62524