

# WAC LIGHTING

## ICBINR 5CCT

### Ceiling and Wall Mount

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

| Model & Size | Color Temp & CRI                          | Watt | Lumens | Finish   |
|--------------|-------------------------------------------|------|--------|----------|
| FM-616G2 6"  | 9CS<br>2700K/3000K/3500K/4000K/5000K - 90 | 16W  | 1050   | WT White |

Example: **FM-616G2-9CS-WT**

#### DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows, which are common in convetional flush mounts.

#### FEATURES

- Multiple LED array for uniform illumination
- Imitates a traditional 6" line voltage recessed downlight with an R30 light bulb
- 5-CCT Switchable between 2700K and 5000K
- Driver installed within the Junction Box, driver dimension: 2.875" dia x 0.875" deep
- 5 year warranty

#### SPECIFICATIONS

|                 |                                                                                                                                                                        |
|-----------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Construction    | Aluminum with translucent diffuser                                                                                                                                     |
| Power:          | 16W                                                                                                                                                                    |
| Input:          | 120 VAC, 50/60Hz                                                                                                                                                       |
| Dimming:        | ELV: 100-5% , TRIAC: 100-5%                                                                                                                                            |
| Light Source:   | Integrated LED                                                                                                                                                         |
| Lens:           | Translucent acrylic diffuser                                                                                                                                           |
| Rated Life:     | 50,000 Hours                                                                                                                                                           |
| Mounting:       | Retrofit over a 5" or 6" recessed can or install over a 4" junction box or a combination 3/0-4/0 electrical box, Can be mounted on ceiling or wall in all orientations |
| Finish:         | Electrostatically Powder Coated: White                                                                                                                                 |
| Operating Temp: | -4°F to 104°F (-20°C to 40°C)                                                                                                                                          |
| Standards:      | ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant                                                                                                           |




#### FINISHES:



White

#### LINE DRAWING



FM-616G2