

WAC LIGHTING

ICBINR 5CCT

Ceiling and Wall Mount

Fixture Type: _____
Catalog Number: _____
Project: _____
Location: _____

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-616G2 6"	9CS 2700K/3000K/3500K/4000K/5000K - 90	16W	1050	WT White

Example: **FM-616G2-9CS-WT**

DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows, which are common in conventional flush mounts.

FEATURES

- Multiple LED array for uniform illumination
- Imitates a traditional 6" line voltage recessed downlight with an R30 light bulb
- 5-CCT Switchable between 2700K and 5000K
- Driver installed within the Junction Box, driver dimension: 2.875" dia x 0.875" deep
- 5 year warranty

SPECIFICATIONS

Construction	Aluminum with translucent diffuser
Power:	16W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-5% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Translucent acrylic diffuser
Rated Life:	50,000 Hours
Mounting:	Retrofit over a 5" or 6" recessed can or install over a 4" junction box or a combination 3/0-4/0 electrical box, Can be mounted on ceiling or wall in all orientations
Finish:	Electrostatically Powder Coated: White
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant




FINISHES:



White

LINE DRAWING



FM-616G2