

WAC LIGHTING

Ion 2" Square 5CCT

New Construction Downlight

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model	Beam	Color Temp & CRI	Lumens	CBCP	Finish
R2DSDN	F 35°	9CS 2700K/3000K/3500K/4000K/5000K - 90	695	2140	WT White

Example: **R2DSDN-F9CS-WT**

DESCRIPTION

Minimum profile downlight with remote driver included for easy remodel or new construction installation.

FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Sold as new construction, may be configured in field for remodel
- Driver included
- 5 year warranty

SPECIFICATIONS

Construction	Die-cast Aluminum with 20-gauge Cold Rolled Steel Driver Box
Power:	9W
Input:	120 VAC, 50/60Hz
Dimming:	ELV: 100-10% , TRIAC: 100-5%
Light Source:	Integrated LED
Lens:	Frosted TIR Lens
Rated Life:	50,000 Hours
Mounting:	New construction housings included with hanger bars
Cut Out:	3"
Finish:	Electrostatically Powder Coated: White
Ceiling Thickness:	1/2" - 1 1/2"
Operating Temp:	-4°F to 104°F (-20°C to 40°C)
Standards:	ETL, cETL, Title 24 JA8 Compliant, Airtight, IC

