

Lotos 4" Square

Adjustable Downlight 5CCT

Model	Beam	Color Temp & CRI	Lumens	СВСР	Finish
R4ESAR	W 45°	2700K/3000K/3500K/4000K/5	740	1000	WT White

Example: R4ESAR-W9CS-WT

For custom requests please contact customs@waclighting.com

DESCRIPTION

The wafer-thin Lotos LED Recessed Kit with remote driver combines high quality light output and efficiency while eliminating the need for a large housing. This innovative design can be installed easily as a remodel or new construction with an optional frame-in kit sold separately. Lotos is available in adownlight version for general ambient lighting and an adjustable version with a gimbal that pivots 360 degrees on a hinge. Now available with 5-CCT options.



FEATURES

- 5-CCT Switchable between 2700K and 5000K
- Multiple LED array for uniform illumination
- · Rotatable multi-axis gimbal ring
- · Driver included
- 5 year warranty

SPECIFICATIONS

Color Temp: 2700K/3000K/3500K/4000K/5000K

Input: 120 -277 VAC,50/60Hz

CRI 90

Dimming: ELV: 100-5%, TRIAC: 100-5%

Rated Life: 50,000 Hours

Mounting: Heavy gauge retention clips secures fixture to ceiling

Standards: ETL, CETL, Title 24 JA8 Compliant, Wet Location Listed

Construction Steel with frosted TIR lens

FINISHES:

Fixture Type:


Project:

Location:

Catalog Number:



LINE DRAWING:





Lotos 4" Square

Adjustable Downlight 5CCT

Fixture Type:
Catalog Number:
Project:
Location:

ACCESSORIES				
	Model	Description	Finish	
	RER-FRAME RER-6	Lotos Lotos		