

WAC LIGHTING

Balto III

Flush Mount 4CCT

Fixture Type:

Catalog Number:

Project:

Location:

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
☐ FMW705605 5"	2700K/3000K/3500K/4000K	☐ BK Black ☐ WT White	13.1W	1125	586

Example: **FMW705605S-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted interior diffuser BALTO III blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

FEATURES

- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW705605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS


Color Temp:	2700K/3000K/3500K/4000K,3000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum body with interior frosted PC diffuser

REPLACEMENT PARTS

RPL-DIF-705605 - BALTO III REPL DIFFUSER




FINISHES:



Black

White

LINE DRAWING



FMW705605

WAC LIGHTING

Balto III

Flush Mount 4CCT

Fixture Type: _____

Catalog Number: _____

Project: _____

Location: _____

Model & Size	Color Temp	Finish	LED Watts	LED Lumens	Delivered Lumens
☐ FMW705605S 5"	☐ 3000K	☐ BK Black ☐ WT White	3.3W	280	131

Example: **FMW705605S-WT**

For custom requests please contact customs@wacighting.com

DESCRIPTION

Minimalist design meets maximum versatility. Defined by its clean circular profile and frosted interior diffuser BALTO III blends sophistication with modern architecture. Built to endure the elements, this versatile fixture is wet rated for outdoor use.

FEATURES


- Built in color temperature adjustability. Switch from 2700K/3000K/3500K/4000K
- Option available for sauna application. Durable and heat resistant. Available in 3000K only (Model#FMW705605S)
- Sauna application operating temperature: Min -4 F/Max 185 F
- Weather resistant powder coated finishes
- ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp:	2700K/3000K/3500K/4000K,3000K
Input:	120V,50/60Hz
CRI	90
Dimming:	ELV: 100-10% , TRIAC: 100-10%
Rated Life:	50,000 Hours
Mounting:	Can be mounted on ceiling or wall in all orientations
Standards:	ETL, cETL, Title 24 JA8 Compliant, ADA, Wet Location Listed
Construction	Aluminum body with interior frosted PC diffuser



FINISHES:



REPLACEMENT PARTS

RPL-DIF-705605 - BALTO III REPL DIFFUSER