ENCLOSED ELECTRONIC 12V

Transformers



Responsible Lighting®

Fixture Type:	
Catalog Number:	
Project:	

PRODUCT DESCRIPTION

Combining Class 2 Transformers in a single package creates a single source to wire multiple runs of low voltage fixtures such as under cabinet and display luminaires.

FEATURES

- 1W minimum load
- Secondary wiring for Class 2 transformers does not require conduit sheathed cable or clamp wiring techniques
- Intrinsically safe, Class 2 transformers permit no greater than a 5 amp current be drawn
- Non-metallic sheathed cable may be used for secondary wiring in walls and ceilings
- Drop down to a smaller gauge wire if space in fixture does not permit secure connection directly with the non-metallic sheathed cable
- · Powers most cabinet fixtures

SPECIFICATIONS

Location:

٦

Construction: Built-in auto reset, soft start, short and overload circuit protection features. The soft start delayed start feature extends lamp life by delaying the abrupt inrush current to the lamp.

Output: 12V

Frequency: 20khz

Dimming: Dimmable with electronic low voltage dimmers. Dimmers should always be installed on the primary side of the transformer.

Details: Enclosure has knockouts on three sides. Screw holes are located on one long side for securing enclosure in place.

Standards: UL Listed

ORDER NUMBER

Model	Input	Output	Min Load	LxWxH	Class 2	Auto Reset	LED Indicator and push in terminals
EN-1260-RB-AR	120VAC	12VAC 60W	1W	6 1/2" x 1 5/8" x 1 1/4"	Yes	Yes	No
EN-1275-RB-AR	120VAC	12VAC 75W	1W	6 1/2" x 1 5/8" x 1 1/4"	No	Yes	No
EN-12100-RB-AR	120VAC	12VAC 100W	1W	6 1/2" x 3" x 1 1/4"	No	Yes	No
EN-12150-RB-AR	120VAC	12VAC 150W	1W	6 1/2" x 3" x 1 1/4"	No	Yes	No
EN-1260-RB2	120VAC	12VAC 1 x 60W	1W	6 5/8" x 1 5/8" x 1 1/4"	Yes	No	No
EN-12120-RB2	120VAC	12VAC 2 x 60W	1W	6" x 3 1/4" x 2 5/8"	Yes	No	Yes
EN-12180-RB2	120VAC	12VAC 3 x 60W	1W	6 3/4" x 3 5/8" x 2 5/8"	Yes	no	Yes
EN-12300-RB2	120VAC	12VAC 5 x 60W	1W	8 1/4" x 4 5/8" x 2 5/8"	Yes	No	Yes
EN-B12PY-AR	120VAC	12VAC 250W	1W	6 1/4" x 3 3/8" x 2 1/8"	No	Yes	No

EN- --

Example: EN-12100-RB-AR

waclighting.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050

Central Distribution Center 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. NOV 2015