

WAC Lighting (Shanghai) Co., Ltd.

Address: No.14, Lane 299, Bi Sheng Road, Zhang Jiang, Pu Dong District,


Shanghai China 201204

Email: sales@waclighting.com.cn Website: www.waclighting.com.cn

LEDme™ PENDANT

GENESIS





Ordering Matrix for Solorail™ Application			
Model Number	Finish of Pendant and Quick Connect™ Adapter (to match rail)		
QPLED311	BN/BN	BN/CH	BN/DB

Ordering Examples (model number /adapter finish): QPLED311-BN/BN

Product Details

Description: Energy efficient LEDme™ Pendant in a modern playful design in

sparkling bubble glass and an elegant Brushed Nickel finish.

Easy installation and height adjustment.

Compatible QP pendant is compatible with 12V Solorail™ systems.

Systems:

LED Engine: Input power: 5W Input Voltage: 12V AC

Fixture lumen: 210 lm

Color temperature: 3000K CRI: 85

Dimming: Dimmable QP pendant with electronic low voltage dimmer when

using a magnetic transformer.

Materials: Die-cast aluminum construction, convex lens, bubble glass ball

and six feet of a low voltage braided wire

Finish: BN / BN- Brushed Nickel / BN- Brushed Nickel

BN / CH- Brushed Nickel / Chrome BN / DB- Brushed Nickel / Dark Bronze

Specification Features

- LED pendant comes with 1830 mm of cable and may be field adjusted to any length.
- Free of projected heat, IR, and UV.
- Dimmable with ELV dimmer (range from 100% to 15%)
- 50,000 hour lifetime
- Replaceable LED module
- 5 years WAC lighting product warranty.