

Vertical Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-12712 12"	3000K 90	PN Polished Nic	kel 11W	772	559

Example: WS-12712-PN

For custom requests please contact customs@waclighting.com

DESCRIPTION

A simple modern design that features a solid crystal block illuminated from within the frame that creates magnificent sparkles as the bubbles within catch the light. Polished Nickelfittings and concealed hardware complete this curiosity inspiring sconce.

FEATURES

- One-inch thick solid crystal with bubbles
- Up & down light
- \bullet Driver installed within the Junction Box, driver dimension: 2.76" x 1.26" x 1.18"
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120-277 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 50000 Hours

Mounting: Can be mounted on wall vertically or upside down

Standards: ETL, cETL, Title 24 JA8-2019 Compliant

Damp Location Listed


Construction: Aluminum hardware with seedy glass diffuser



FINISHES:



Polished Nickel





Vertical Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-12713 13"	3000K 90	PN Polished Nickel	8W	392	139

Example: WS-12713-PN

•For 277V special order, add an "F" before the finish: WS-12713F-PN

For custom requests please contact customs@waclighting.com

DESCRIPTION

A simple modern design that features a solid crystal block illuminated from within the frame that creates magnificent sparkles as the bubbles within catch the light. Polished Nickelfittings and concealed hardware complete this curiosity inspiring sconce.

FEATURES

- · One-inch thick solid crystal with bubbles
- Up & down light
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8-2019 Compliant

Damp Location Listed


Construction: Aluminum hardware with seedy glass diffuser



FINISHES:



Polished Nickel





Vertical Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish		Watt	LED Lumens	Delivered Lumens
WS-12718 18"	3000K 90	PN	Polished Nickel	15.9W	771	333

Example: WS-12718-PN

•For 277V special order, add an "F" before the finish: WS-12718F-PN

For custom requests please contact customs@waclighting.com

DESCRIPTION

A simple modern design that features a solid crystal block illuminated from within the frame that creates magnificent sparkles as the bubbles within catch the light. Polished Nickelfittings and concealed hardware complete this curiosity inspiring sconce.

FEATURES

- · One-inch thick solid crystal with bubbles
- Up & down light
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8-2019 Compliant

Damp Location Listed


Construction: Aluminum hardware with seedy glass diffuser



FINISHES:



Polished Nickel





Vertical Wall Sconce 3000K

Fixture Type:	
Catalog Number:	
Project:	
Location:	

Model & Size	Color Temp & CRI	Finish	Watt	LED Lumens	Delivered Lumens
WS-12724 24"	3000K 90	PN Polished Nickel	16W	730	326

Example: WS-12724-PN

•For 277V special order, add an "F" before the finish: WS-12724F-PN

For custom requests please contact customs@waclighting.com

DESCRIPTION

A simple modern design that features a solid crystal block illuminated from within the frame that creates magnificent sparkles as the bubbles within catch the light. Polished Nickelfittings and concealed hardware complete this curiosity inspiring sconce.

FEATURES

- · One-inch thick solid crystal with bubbles
- Up & down light
- · ACLED driverless technology
- 5 year warranty

SPECIFICATIONS

Color Temp: 3000K

Input: 120 VAC,50/60Hz

CRI: 90

Dimming: ELV: 100-10% Rated Life: 54000 Hours

Mounting: Can be mounted on wall in all orientations

Standards: ETL, cETL,Title 24 JA8-2019 Compliant

Damp Location Listed

Construction: Aluminum hardware with seedy glass diffuser



FINISHES:



Polished Nickel

