

## HANDLESETS

<b>Door Prep</b>	Deadbolt: Cross Bore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"	<b>Strikes</b>	Deadbolt: 1-1/8" x 2 - 3/4" Specify round corner or square corner Handle: 2-1/4" full lip Specify round corner or square corner Other options available
<b>Backset</b>	Deadbolt: Adjustable to 2-3/8" or 2-3/4" Handle: Adjustable to 2-3/8" or 2-3/4"	<b>Bolt</b>	Deadbolt: 1" steel Handle: 1/2" throw. Nickel plated
<b>Door</b>	1-3/4" doors standard. 2-1/4" doors optional	<b>Door Handing</b>	Reversible for right or left-hand doors
<b>Thickness</b>	Not designed for use on 1-3/8" doors.	<b>ANSI/BHMA</b>	A156.5 Grade 2 (for deadbolt)
<b>Cylinder</b>	SmartKey or KW or WS 5pin	<b>ADA</b>	N/A
<b>Faceplate</b>	1" x 2-1/4" Specify round corner or square corner or drive-in	<b>UL</b>	N/A

## LEVERS

<b>Door Prep</b>	Cross Bore 2-1/8" Edge Bore 1" Latch Face 1" x 2-1/4"	<b>Strikes</b>	2-1/4" full lip Specify round corner or square corner Other options available
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional	<b>Bolt</b>	1/2" throw nickel plated
<b>Door</b>	1-3/8" - 1-3/4" doors standard	<b>Door Handing</b>	Specify handing only with Inactive levers
<b>Thickness</b>	2-1/4" doors optional on GLA101 and GLA535 models	<b>ANSI/BHMA</b>	A156.2 Grade 2
<b>Cylinder</b>	SmartKey or KW or WS 5pin	<b>ADA</b>	Functions GLA 101 and GLA 12 satisfy section ... 4.13.9. ADA requirement
<b>Faceplate</b>	1" x 2-1/4" Specify round corner, square corner or drive-in	<b>UL</b>	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.

## KNOBS

<b>Door Prep</b>	Cross Bore: 2-1/8" Edge Bore: 1" Latch Face: 1"x 2-1/4"	<b>Strikes</b>	2-1/4" full lip Specify round corner or square corner Other options available
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4" UL 2-3/4" standard 2-3/8" optional	<b>Bolt</b>	1/2" throw nickel plated
<b>Door</b>	1 - 3/8" - 1-3/4" doors standard	<b>Door Handing</b>	Reversible for right- or left-hand doors.
<b>Thickness</b>	2-1/4" doors optional 2-1/4" doors optional on GA 101 and GLA 551 models only	<b>ANSI/BHMA</b>	A156.2 Grade 2
<b>Cylinder</b>	SmartKey or KW or WS 5pin	<b>ADA</b>	N/A
<b>Faceplate</b>	1" x 2-1/4" Specify round corner, square corner or drive-in	<b>UL</b>	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.

## DEADBOLTS

<b>Door Prep</b>	Crossbore 2-1/8" or 1-1/2" Edge Bore 1" Latch Face 1" x 2-1/4"	<b>Strikes</b>	1-1/8" x 2-3/4" Specify round corner or square corner
<b>Backset</b>	Adjustable to 2-3/8" or 2-3/4"	<b>Bolt</b>	1" throw Steel
<b>Door</b>	1-3/8" - 1-3/4" Standard	<b>Door Handing</b>	Reversible for right or left-hand doors
<b>Thickness</b>	2-1/4" Optional	<b>ANSI/BHMA</b>	A156.5 Grade 2
<b>Cylinder</b>	SmartKey or KW or WS 5pin	<b>ADA</b>	Interior turn piece meets 4.13.9 ADA requirements
<b>Faceplate</b>	1" x 2-1/4" Specify round corner, square corner or drive-in	<b>UL</b>	Meets 3 hour fire rating for all UL functions when fronted latches used. Meets 20 minute with drive-in latch.